

Title (en)
Dampening device

Title (de)
Feuchtwerk

Title (fr)
Dispositif de mouillage

Publication
EP 0722830 A3 19970102 (DE)

Application
EP 96100390 A 19960112

Priority
DE 19501147 A 19950117

Abstract (en)
[origin: EP0722830A2] The application roller (2) can be adjusted w.r.t. the formed cylinder (1), while an intermediate roller (3) contacts the application and an immersion roller (4). The intermediate and immersion rollers can be moved away from the application roller and from each other, with thin contact positions reproducible. All rollers are adjustable. The application roller is directly mounted in a bearing shield (5) in the machine frame, while the other rollers are thus mounted via an intermediate location of their adjusting members. The bearing shield is swivelable in the forme cylinder direction.

IPC 1-7
B41F 7/40

IPC 8 full level
B41F 7/26 (2006.01); **B41F 7/40** (2006.01)

CPC (source: EP)
B41F 7/26 (2013.01); **B41F 7/40** (2013.01)

Citation (search report)
• [YDA] DE 3005664 A1 19800821 - DAHlgren Mfg Co
• [Y] DE 461990 C 19280629 - GEORGE MANN AND COMPANY LTD
• [Y] US 3168037 A 19650202 - DAHlgren Harold P
• [Y] DE 2822350 A1 19781207 - NEBIOLO SPA
• [A] DE 3539254 A1 19861009 - DIDDE GRAPHIC SYSTEMS CORP [US]
• [AD] DE 4312523 A1 19941020 - HEIDELBERGER DRUCKMASCH AG [DE]

Cited by
DE102008061599A1; DE102005015791B4; US7225735B2

Designated contracting state (EPC)
DE FR GB SE

DOCDB simple family (publication)
DE 19501147 A1 19960718; DE 59601570 D1 19990512; EP 0722830 A2 19960724; EP 0722830 A3 19970102; EP 0722830 B1 19990407

DOCDB simple family (application)
DE 19501147 A 19950117; DE 59601570 T 19960112; EP 96100390 A 19960112