

Title (en)
Locking device for switch blades

Title (de)
Verschlussvorrichtung für Weichenzungen

Title (fr)
Dispositif de verrouillage pour aiguilles mobiles

Publication
EP 0723901 A3 19970702 (DE)

Application
EP 96100987 A 19960124

Priority
DE 19502105 A 19950124

Abstract (en)
[origin: EP0723901A2] The device includes a sliding rod (14) which is guided on a rolling body (20) such as a cylindrical roller which is mounted at a specific distance from the jaw rail (10). The distance between the rotary axis of the roller and the rail is adjustable. A closure member (22) fixed on the jaw rail is passed through by the closure element (16) and sliding rod and the rotational shaft of the roller is guided in the closure member. The closure member is axially symmetrical and can be fixed each side of the jaw rail.

IPC 1-7
B61L 5/10

IPC 8 full level
B61L 5/10 (2006.01); **E01B 7/02** (2006.01)

CPC (source: EP)
B61L 5/10 (2013.01); **E01B 2202/08** (2013.01)

Citation (search report)

- [Y] DE 3131499 A1 19830224 - RUHRTALER GESENKSCHMIEDE F W W [DE]
- [DY] DE 4014248 A1 19911107 - BUTZBACHER WEICHENBAU GMBH [DE]
- [Y] FR 550064 A 19230226
- [Y] EP 0624508 A1 19941117 - SIEMENS INTEGRA VERKEHRSTECHNI [CH]
- [Y] DE 2817782 A1 19791025 - ELEKTRO THERMIT GMBH
- [A] DE 2352017 A1 19750430 - RUHRTALER GESENKSCHMIEDE F W W

Cited by
EP2402505A1; EP1020341A1; CN115320666A; CN101870300A; KR100578407B1; WO0114200A1; WO0002759A1; WO0151332A1; US6616105B2; US8245984B2; DE102008060229A1

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0723901 A2 19960731; EP 0723901 A3 19970702; EP 0723901 B1 20020417; AT E216328 T1 20020515; DE 19502105 A1 19960725; DE 19502105 C2 20000427; DE 19502105 C5 20041230; DE 59609077 D1 20020523; DK 0723901 T3 20020729; ES 2171571 T3 20020916

DOCDB simple family (application)
EP 96100987 A 19960124; AT 96100987 T 19960124; DE 19502105 A 19950124; DE 59609077 T 19960124; DK 96100987 T 19960124; ES 96100987 T 19960124