

Title (en)

Supporting device for a set of juxtaposable headers

Title (de)

Stützvorrichtung für eine Gruppe miteinander verbindbarer Halterungen

Title (fr)

Dispositif de support pour une batterie d'embases juxtaposables

Publication

**EP 0724081 A1 19960731 (FR)**

Application

**EP 96400131 A 19960119**

Priority

FR 9500964 A 19950127

Abstract (en)

The method of fixing a bank of pneumatic base plates (1) to a frame (5) has at each of the ends of the bank an end plate (10) having a connecting face (18) with end plate of the bank of base plates (1) which corresponds with that of the bank of base plates, and the method of connecting the feed and exhaust channels of the bank to respectively, a pressure source and exhaust chamber associated with the frame (5). It is characterised in that the unit contains two hollowed out and parallel transverse arms (7,8) whose interior space in one of them, is in communication with the exhaust chamber of the frame (5). Each possesses a face (7a,8a) extending in a common plane forming the mounting plane of the end plates of the bank of base plates (1) and having on this face, ports (22,23) which connect with the interior spaces of each end plate (10). This facing plane (20) is at right angles to the mating plane (18) of the end plate (10) with the face (20) of the base plates (1). An internal porting (21a) in the end plate (10) joins the exhaust port in the bank (1) to the exhaust chamber in the frame (5) via the ports (22,23) in the corresponding transverse arms.

Abstract (fr)

Le dispositif de fixation comporte un embout (10) qui est juxtaposable par une face (18) à une embase (1) d'extrémité de batterie et qui comporte une face (20) perpendiculaire à la face (18) qui comprend les orifices (21a) de canaux internes (21) formant collecteurs des canaux (14) d'échappement des embases, ces orifices (21a) étant placés en regard d'orifices (22) pourvus dans une traverse (7) creuse pour conduire les gaz d'échappement collectés dans un pot de détente appartenant à un bâti auquel l'espace intérieur de la traverse creuse (7) est relié. <IMAGE>

IPC 1-7

**F15B 13/00**

IPC 8 full level

**F15B 13/00** (2006.01); **F15B 13/08** (2006.01)

CPC (source: EP)

**F15B 13/0817** (2013.01); **F15B 13/0821** (2013.01); **F15B 13/0832** (2013.01)

Citation (search report)

- [A] GB 2143898 A 19850220 - FESTO KG
- [A] FR 2526092 A1 19831104 - FESTO MASCHF STOLL G [DE]
- [A] FR 2531151 A1 19840203 - BENNES MARREL [FR]

Designated contracting state (EPC)

BE DE ES GB IT

DOCDB simple family (publication)

**EP 0724081 A1 19960731**; FR 2730017 A1 19960802; FR 2730017 B1 19970228

DOCDB simple family (application)

**EP 96400131 A 19960119**; FR 9500964 A 19950127