

Title (en)

PROCESS FOR DRYING AUTOMOBILE PAINTS

Title (de)

VERFAHREN ZUM TROCKEN VON AUTOMOBILLACKEN

Title (fr)

PROCEDE POUR LE SECHAGE DE PEINTURES D'AUTOMOBILES

Publication

EP 0724706 B1 19971210 (DE)

Application

EP 94930967 A 19941021

Priority

- DE 4336857 A 19931028
- EP 9403467 W 19941021

Abstract (en)

[origin: WO9512102A1] In order to obtain the smoothest possible paint surface on automobiles, the invention proposes that the heating phase be interrupted when an object temperature of about 65 DEG C is attained. Said object temperature is then maintained for at least 2 and at the most 3 1/2 minutes. The heating phase is then resumed until the holding temperature is attained.

IPC 1-7

F26B 3/30

IPC 8 full level

F26B 3/28 (2006.01); **F26B 3/30** (2006.01)

CPC (source: EP US)

F26B 3/283 (2013.01 - EP US); **F26B 3/30** (2013.01 - EP US); **F26B 2210/12** (2013.01 - EP US)

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

DE 4336857 A1 19950504; DE 59404793 D1 19980122; EP 0724706 A1 19960807; EP 0724706 B1 19971210; US 5689899 A 19971125; WO 9512102 A1 19950504

DOCDB simple family (application)

DE 4336857 A 19931028; DE 59404793 T 19941021; EP 9403467 W 19941021; EP 94930967 A 19941021; US 63762796 A 19960429