

Title (en)
CANDLESTICK

Title (de)
KERZENTRÄGER

Title (fr)
BOUGEOIR

Publication
EP 0725914 B1 19980107 (DE)

Application
EP 94930179 A 19941017

Priority
• DE 4337397 A 19931030
• DE 4403369 A 19940204
• EP 9403410 W 19941017

Abstract (en)
[origin: WO9512783A1] A candlestick for a candle or a taper with a heat-conducting burner pan (2) and a holder (3C) arranged centrally therein which is a heat conducting ring (3C) in which the lower core region of the candle or taper is fitted and which is surrounded by a lower outer region of the candle or taper, and in which the height of the heat conducting ring (3C) is about half that of the candle flame, its width is about double the diameter of the candle flame and has lateral ventilation apertures (30C), at least one of which extends as an inlet aperture for liquefied candle material to the lowest point of the holder and in which a wick holder (HW) is arranged centrally on the base of the heat conducting ring (3C) and the holder (2) and the wick holder (HW) are secured to be heat-insulated. The wick holder (HW) consists of a coil of wire and makes it possible to burn off the residue of the wick.

IPC 1-7
F21V 35/00

IPC 8 full level
F21V 35/00 (2006.01)

CPC (source: EP)
F21V 35/00 (2013.01)

Cited by
EP2189717A1; DE102006051806B3; DE102008037586B3

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB IE IT LI NL SE

DOCDB simple family (publication)
WO 9512783 A1 19950511; AT E161936 T1 19980115; AU 7938094 A 19950523; DE 4403369 A1 19950810; DE 59404981 D1 19980212; DK 0725914 T3 19980907; EP 0725914 A1 19960814; EP 0725914 B1 19980107

DOCDB simple family (application)
EP 9403410 W 19941017; AT 94930179 T 19941017; AU 7938094 A 19941017; DE 4403369 A 19940204; DE 59404981 T 19941017; DK 94930179 T 19941017; EP 94930179 A 19941017