

Title (en)

Screw rotor pump

Title (de)

Schraubenspindelpumpe

Title (fr)

Pompe à rotors à vis

Publication

**EP 0727581 A1 19960821 (DE)**

Application

**EP 96105318 A 19910307**

Priority

- DE 4007273 A 19900308
- EP 91710004 A 19910307

Abstract (en)

The screw spindle pump has a drive spindle and at least one running spindle. They are mounted in the recess of a housing between a suction chamber and a pressure chamber. The pressure-side profile run-out of the spindle (14) is conically turned at the OD (d) and the angle of inclination (w) of the conical surface (43) lies below 10 deg.

Abstract (de)

Bei einer Schraubenspindelpumpe mit einer Antriebsspindel (14) und wenigstens einer Laufspindel, die in einer Ausnehmung eines sie umgebenden Gehäuses zwischen einem Saugraum und einem Druckraum gelagert sind, ist die Zahndicke (b) der Antriebsspindel (14) zu ihrem Profilauslauf hin vermindert. <IMAGE>

IPC 1-7

**F04C 2/16**; **F04C 15/00**

IPC 8 full level

**F04C 2/16** (2006.01); **F04C 2/08** (2006.01); **F04C 14/00** (2006.01); **F04C 15/00** (2006.01)

CPC (source: EP KR US)

**F04C 2/084** (2013.01 - EP US); **F04C 15/0049** (2013.01 - EP US); **F04C 18/16** (2013.01 - KR)

Citation (search report)

[X] US 2652192 A 19530915 - ROLAND CHILTON

Designated contracting state (EPC)

AT GB IT SE

DOCDB simple family (publication)

**EP 0451085 A2 19911009**; **EP 0451085 A3 19920708**; **EP 0451085 B1 19980812**; AT E169721 T1 19980815; AT E176717 T1 19990215; BR 9100993 A 19911105; EP 0727581 A1 19960821; EP 0727581 B1 19990210; JP 3036874 B2 20000424; JP H05231341 A 19930907; KR 0177815 B1 19990415; KR 910017081 A 19911105; US 5123821 A 19920623

DOCDB simple family (application)

**EP 91710004 A 19910307**; AT 91710004 T 19910307; AT 96105318 T 19910307; BR 9100993 A 19910308; EP 96105318 A 19910307; JP 6913891 A 19910308; KR 910003767 A 19910308; US 61767890 A 19901126