

Title (en)  
Ventilator

Title (de)  
Lüfter

Title (fr)  
Aérateur

Publication  
**EP 0730126 A2 19960904 (EN)**

Application  
**EP 96301261 A 19960226**

Priority  
GB 9504105 A 19950301

Abstract (en)

A glazed-in ventilator assembly comprises an elongate first element 5 having a longitudinal flange 6 for locating in a rebate 2 of the frame 3 of a door or window, an elongate second element 7 having a longitudinal channel 8 for reception of the marginal edge of glazing 9, the first and second elements 5,7 being rigidly connected together, and an elongate third element 4 connected to the first element 5 for pivotal movement to control airflow through the assembly. A spring 27 has a cantilever spring leg 28 co-operable with a free edge 22 of the third element 4 remote from the pivot axis for holding the third element 4 in any selected one of a range of open positions and the free edge 22 is arranged for snap action engagement with a rib 29 at the root of the spring leg 28 to hold the third element in a closed position. A respective end cap 32 (Figure 2) is fitted to each end of the assembly. <IMAGE>

IPC 1-7

**F24F 13/18**

IPC 8 full level

**F24F 13/18** (2006.01)

CPC (source: EP)

**F24F 13/18** (2013.01)

Cited by

NL1004665C2; NL1018166C2; NL1010139C2; EP2134917A4; EP2048318A2; WO02097339A1; WO2006131125A1

Designated contracting state (EPC)

DE DK GB IE NL

DOCDB simple family (publication)

**EP 0730126 A2 19960904; EP 0730126 A3 19971210**; GB 2299663 A 19961009; GB 9504105 D0 19950419

DOCDB simple family (application)

**EP 96301261 A 19960226**; GB 9504105 A 19950301