

Title (en)
Device for covering a wall aperture

Title (de)
Vorrichtung zum Verschliessen von Maueröffnungen

Title (fr)
Dispositif pour la fermeture d'une fermeture dans un mur

Publication
EP 0731245 A3 19970102 (DE)

Application
EP 95118942 A 19951201

Priority
DE 19508645 A 19950310

Abstract (en)
[origin: EP0731245A2] The closure comprises a plate-like body (2) having a circumferential flange (5) for bearing on the outside of the wall facing the water and round the entire perimeter a first groove (6) holding an inflatable hose (7) of rubber elastic material. When inflated the hose projects out of the groove to adjoin the surface of the wall defining the window or door opening. A sealing ring (11) can be fixed on the inside of the flange. The plate like body can have on the inside of an outer cover plate (9) forming the flange a frame containing the circumferential first groove. The plate-like body is solid and in one piece. A non-return valve (12) is provided for inflating the hose.

IPC 1-7
E06B 5/10

IPC 8 full level
E06B 7/23 (2006.01); **E06B 9/00** (2006.01)

CPC (source: EP)
E06B 7/2318 (2013.01); **E06B 9/00** (2013.01); **E06B 2009/007** (2013.01)

Citation (search report)

- [XA] DE 3622733 A1 19880107 - RIENKS GERD [DE]
- [XA] DE 9402224 U1 19940414 - SCHEMMANN STEFFEN DR [DE], et al
- [X] DE 9400710 U1 19940505 - TORLIT GMBH ISOLIER U BRANDSCH [DE]

Cited by
DE19861242C2; EP0898041A3; AT412414B; DE102013214547A1; DE19857882C2; DE19726960C1; GB2346168A; CN108915467A; NL1010608C2; US11293285B2; DE19707394A1; DE19707394C2; DE10301320B4; GB2342377A; GB2342377B; CN111734269A; GB2368874A; GB2342948A; GB2342948B; EP0841458A3; CN114033285A; WO2007068225A1; WO2007007044A1; BE1015287A3; WO2012044535A3; WO2009003924A1

Designated contracting state (EPC)
AT BE CH DE DK FR GB IT LI NL

DOCDB simple family (publication)
EP 0731245 A2 19960911; EP 0731245 A3 19970102

DOCDB simple family (application)
EP 95118942 A 19951201