

Title (en)

MECHANISM FOR EJECTION CUTOFF PARTS IN A CUTTING-OFF DEVICE

Title (de)

EINRICHTUNG ZUM AUSSCHIEBEN VON ZERTRENNTEN TEILEN IN EINER TRENNVORRICHTUNG

Title (fr)

SYSTEME D'EJECTION DE PARTIES COUPEES DANS UN DISPOSITIF DE TRONCONNAGE

Publication

EP 0735933 A1 19961009 (DE)

Application

EP 95905073 A 19941216

Priority

- DE 4343483 A 19931220
- EP 9404192 W 19941216

Abstract (en)

[origin: WO9517276A1] The mechanism for ejecting cutoff parts of the workpiece consists of a blade (11) which is inserted or pivoted into the cutting gap (TS) in the workpiece (7) against the machining direction of the cutting-off tool, preferably through a slot (13) in the workbench (9). After the blade (11) has been inserted or pivoted in, it is withdrawn horizontally from the machining space (AR) along the surface of the workbench (9), taking the section of the workpiece concerned with it. Thus the blade (11) performs in succession a substantially vertical or pivoting movement and then a horizontal movement to clear the workbench (9). The blade (11) itself may be provided on its side facing the workbench (9) with means for removing machining residues, e.g. a swarf brush. As the distance and direction especially of the blade's horizontal movement can be controlled, the sections can be sorted by allocating severed parts of the workpiece to different delivery positions in front of or behind the cutting-off tool, thus further rationalising the process.

IPC 1-7

B23D 47/04; **B23D 59/00**; **B23Q 11/00**

IPC 8 full level

B23D 47/04 (2006.01); **B23D 59/00** (2006.01); **B23Q 11/00** (2006.01)

CPC (source: EP)

B23D 47/042 (2013.01); **B23D 59/006** (2013.01); **B23Q 11/0042** (2013.01)

Citation (search report)

See references of WO 9517276A1

Designated contracting state (EPC)

AT CH DE LI

DOCDB simple family (publication)

DE 4343483 A1 19950622; EP 0735933 A1 19961009; WO 9517276 A1 19950629

DOCDB simple family (application)

DE 4343483 A 19931220; EP 9404192 W 19941216; EP 95905073 A 19941216