

Title (en)
Guillotine-type cutter

Title (de)
Planschneidmaschine

Title (fr)
Guillotine

Publication
EP 0736362 B1 19981125 (DE)

Application
EP 96103023 A 19960229

Priority
DE 19512106 A 19950403

Abstract (en)
[origin: EP0736362A2] The cutting machine includes at least two adjustable devices set at a distance from each other in the cutter bar (9) to support the cutter (10). Each device (20) is supported on the spine (28) of the cutter by a pressure member (29) which is hard at least in the contact area with the relevant adjustable device. The adjustable device (20) can have a cam disc (22) or set screw. The cam disc is connected to a support shaft (24) mounted in the cutter (10) at right angles to the disc. The cam disc can have a spirally extending circumferential surface section (23) to contact the pressure member.

IPC 1-7
B26D 7/26; **B26D 1/08**

IPC 8 full level
B26D 1/08 (2006.01); **B26D 7/26** (2006.01)

CPC (source: EP US)
B26D 1/08 (2013.01 - EP US); **B26D 7/2628** (2013.01 - EP US); **Y10T 83/8867** (2015.04 - EP US); **Y10T 83/9483** (2015.04 - EP US); **Y10T 83/9486** (2015.04 - EP US)

Cited by
EP1060857A1; DE19726993A1; US6155151A; DE202007018569U1

Designated contracting state (EPC)
CH DE ES FR GB IT LI NL PT SE

DOCDB simple family (publication)
EP 0736362 A2 19961009; **EP 0736362 A3 19970205**; **EP 0736362 B1 19981125**; DE 19512106 C1 19961107; DE 59600854 D1 19990107; ES 2125069 T3 19990216; JP H08267395 A 19961015; SG 77112 A1 20001219; US 5784940 A 19980728

DOCDB simple family (application)
EP 96103023 A 19960229; DE 19512106 A 19950403; DE 59600854 T 19960229; ES 96103023 T 19960229; JP 11180396 A 19960329; SG 1996006547 A 19960326; US 61548696 A 19960312