

Title (en)

Method and device for separating a screen on a flat screen textile printing machine

Title (de)

Vorrichtung und Verfahren zum Freimachen eines Siebs einer flachen Siebdruckmaschine

Title (fr)

Procédé et dispositif pour libérer un pochoir d'une machine à imprimer à plat en sérigraphie

Publication

EP 0736378 B1 19991229 (EN)

Application

EP 95116618 A 19951021

Priority

JP 8222595 A 19950407

Abstract (en)

[origin: EP0736378A1] When a color paste is squeegeed by a squeegee in printing the fabric by a flat screen textile printing machine, a screen (118 b) is separated from the surface of the fabric by raising a screen frame (118 a) at the side of start of squeegee (114) travel at the same time as, or with a slight time lag after, the start of squeegeeing, while squeegeeing is carried out. <IMAGE>

IPC 1-7

B41F 15/08

IPC 8 full level

B41F 15/08 (2006.01); **B41F 15/36** (2006.01); **B41M 1/12** (2006.01)

CPC (source: EP KR)

B41F 15/00 (2013.01 - KR); **B41F 15/085** (2013.01 - EP)

Designated contracting state (EPC)

CH DE FR GB IT LI NL

DOCDB simple family (publication)

EP 0736378 A1 19961009; **EP 0736378 B1 19991229**; BR 9504482 A 19970902; CN 1072108 C 20011003; CN 1128210 A 19960807; DE 69514210 D1 20000203; DE 69514210 T2 20000511; JP H08276563 A 19961022; KR 100365850 B1 20030306; KR 960037305 A 19961119; SG 63530 A1 19990330; TW 290601 B 19961111

DOCDB simple family (application)

EP 95116618 A 19951021; BR 9504482 A 19951020; CN 95118023 A 19951020; DE 69514210 T 19951021; JP 8222595 A 19950407; KR 19950036132 A 19951019; SG 1995001593 A 19951019; TW 84111044 A 19951019