

Title (en)
Die cutting device for a printing device

Title (de)
Schneid-Stanzvorrichtung für eine Druckvorrichtung

Title (fr)
Dispositif de découpage à l'emporte-pièce pour un dispositif d'impression

Publication
EP 0736381 A3 19970226 (EN)

Application
EP 96201860 A 19920918

Priority

- EP 92420320 A 19920918
- JP 26850191 A 19910919
- JP 26850291 A 19910919
- JP 26850391 A 19910919
- JP 8430391 U 19910919
- JP 8430591 U 19910919

Abstract (en)
[origin: EP0540430A2] A printing device (1) is disclosed comprising a duplicator (3) for performing intermittent printing onto a strip-shaped article subjected to printing (S1) supplied from a paper supply device (2) using a printing impression-roll which performs positive or reversed rotation while performing forward or backward movement in a direction perpendicular to a sending direction of the strip-shaped article subjected to printing (S1); a die cutting device (5) for punching a strip-shaped printed article (S2) printed by the duplicator (3) into a suitable shape; and a punched residue winding device (6) for winding a punched residue (A) after punching by the die cutting device (5); wherein the duplicator (3) is provided with an ink applying device (11) which allows a forward-step application roller for applying ink during the forward step onto a printing impression face of the printing impression roll which performs positive or reversed rotation while performing forward or backward movement, and a backward-step application roller for applying ink during the backward step to contact with each of the individual ink rolls which rotate in the reversed direction with respect to the rotation direction of each of the application rollers so as to adhere ink onto each of the application rollers, the ink applying device comprising a bottling roll (13) for sending ink from an ink tank (12); an access roll (15) which performs rotational movement with a support arm (14) so as to suitably abut against the bottling roll (13), and a fixed metal roll (18) and a kneading roll (19) for adhering ink supplied by the bottling roll (13) and the access roll (15) onto the ink rolls (16,17), the kneading roll (19) being rotated at a high speed so as to adhere ink onto the kneading roll (19), the ink rolls (16,17) and the fixed metal roll (18) for circulating the ink; whereby the formation is made so as to equalize adhesion of ink onto the application rollers.

IPC 1-7
B41F 17/00

IPC 8 full level
B26F 1/40 (2006.01); **B41F 13/12** (2006.01); **B41F 17/00** (2006.01); **B41F 31/00** (2006.01); **B41F 33/00** (2006.01)

CPC (source: EP)
B26F 1/40 (2013.01); **B41F 13/12** (2013.01); **B41F 17/00** (2013.01); **B41F 31/00** (2013.01); **B41F 33/0036** (2013.01); **B41F 33/0081** (2013.01)

Citation (search report)

- [A] US 4681004 A 19870721 - WALDNER KURT [US]
- [A] US 5042352 A 19910827 - LUX ARTHUR J [US]
- [A] DE 8434604 U1 19870619

Designated contracting state (EPC)
CH DE FR GB LI

DOCDB simple family (publication)
EP 0540430 A2 19930505; EP 0540430 A3 19930825; EP 0540430 B1 19971229; DE 69223740 D1 19980205; DE 69223740 T2 19980514; DE 69228328 D1 19990311; DE 69228328 T2 19990715; EP 0705784 A2 19960410; EP 0705784 A3 19961218; EP 0736381 A2 19961009; EP 0736381 A3 19970226; EP 0736381 B1 19990127; EP 0775660 A2 19970528; EP 0775660 A3 19970709

DOCDB simple family (application)
EP 92420320 A 19920918; DE 69223740 T 19920918; DE 69228328 T 19920918; EP 95117038 A 19920918; EP 96201860 A 19920918; EP 96202941 A 19920918