

Title (en)

Device for starting and stopping printing and method for controlling such device

Title (de)

Vorrichtung zur Druckan- und -abstellung und Verfahren zum Steuern dieser Vorrichtung

Title (fr)

Dispositif pour enclencher ou déclencher l'impression et procédé de contrôle de ce dispositif

Publication

EP 0736384 B1 19990506 (DE)

Application

EP 96105039 A 19960329

Priority

DE 19513378 A 19950408

Abstract (en)

[origin: EP0736384A1] The device includes an eccentric bearing and setting means and a separate pressure setter (11) which is connected in series with the setting means (1,2) which set the rubber blanket cylinder (GT) relative to the counter pressure cylinder (GD). The two setting means act on the eccentric bearing (10) through a ternary member (5). The pressure setting comprises a screw drive formed by a motor-driven threaded spindle (14) and a nut (15) screwed thereon. A ternary member (16) mounted rotatable about a point fixed on the frame is attached to the nut and the setting means is supported on a further articulation point of the ternary member.

IPC 1-7

B41F 33/08; **B41F 13/28**

IPC 8 full level

B41F 13/24 (2006.01); **B41F 13/28** (2006.01); **B41F 33/08** (2006.01)

CPC (source: EP US)

B41F 13/28 (2013.01 - EP US); **B41F 33/08** (2013.01 - EP US)

Cited by

DE102015204557B4; DE102018206126A1; EP1199164A3; DE102015204557A1

Designated contracting state (EPC)

AT CH DE FR GB IT LI

DOCDB simple family (publication)

EP 0736384 A1 19961009; **EP 0736384 B1 19990506**; AT E179654 T1 19990515; DE 19513378 A1 19961010; DE 59601802 D1 19990610; JP 2911815 B2 19990623; JP H08281903 A 19961029; US 5649482 A 19970722

DOCDB simple family (application)

EP 96105039 A 19960329; AT 96105039 T 19960329; DE 19513378 A 19950408; DE 59601802 T 19960329; JP 8413696 A 19960405; US 62915196 A 19960408