

Publication

EP 0737432 A3 19961030

Application

EP 96810212 A 19960403

Priority

CH 109695 A 19950413

Abstract (en)

[origin: EP0737432A2] Each hook (1) consists of a U-shaped part (20) shaped from flat material and gripping round the flat oval shape of the support bar. A hook arm (10) is joined to the U-shaped part. The U-shaped bracket part consists of a bottom half curve (21) with a free end (22) and a top curve (27) leading to the arm. A fitment (11) on the hook arm is positioned over the half curve and, together with the free end and the fitment, forms an access opening (2). The support bar consists of two spaced apart convex walls (32) or two parallel walls. The end (12) of the hook arm protruding into the room has an upward bent part (13).

IPC 1-7

A47F 5/08; **A47F 7/24**

IPC 8 full level

A47F 5/08 (2006.01); **A47F 7/24** (2006.01)

CPC (source: EP)

A47F 5/0838 (2013.01); **A47F 7/24** (2013.01)

Citation (search report)

- [DA] DE 3317421 A1 19840322 - WANZL KG RUDOLF [DE]
- [A] US 4316547 A 19820223 - VARON DAVID S
- [A] GB 2207853 A 19890215 - INTERIOR SYSTEMS

Cited by

DE202008000448U1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL

DOCDB simple family (publication)

EP 0737432 A2 19961016; **EP 0737432 A3 19961030**; **EP 0737432 B1 19980902**; AT E170373 T1 19980915; DE 59600497 D1 19981008

DOCDB simple family (application)

EP 96810212 A 19960403; AT 96810212 T 19960403; DE 59600497 T 19960403