

Title (en)  
Method for providing a frame with an espagnolette

Title (de)  
Verfahren zur Ausstattung eines Flügels mit einem Treibstangenbeschlag

Title (fr)  
Méthode pour équiper un battant d'une espagnolette

Publication  
**EP 0740039 B1 19991103 (DE)**

Application  
**EP 96103862 A 19960312**

Priority  
DE 19515071 A 19950428

Abstract (en)  
[origin: EP0740039A1] There is a bar mechanism on one side of the movable door- or window-frame (1), comprising a central actuating unit (7) and two corner fittings (8,9). The overall working length is adjustable by fine-toothed coupling halves (15) engaging together. There is a short coupling half (16) at each end of the driving rod (12) in the actuating unit, which is engaged in different positions by a long half (17) on the respective corner-fitting rod (13,14). Where there is a parallel covering rail for each rod or bar, the latter can protrude beyond it for the adjustment distance, the rail being cut off as necessary, and the longer coupling halves can also be cut off as necessary.

IPC 1-7  
**E05C 9/20**; **E05C 9/06**

IPC 8 full level  
**E05C 9/06** (2006.01); **E05C 9/20** (2006.01)

CPC (source: EP)  
**E05C 9/066** (2013.01); **E05C 9/20** (2013.01); **E05C 9/24** (2013.01)

Cited by  
EP0841450A1; EP2295687A3; CN101932784A; EA016848B1; CN103899167A; GB2518464A; GB2561141A; GB2561141B; WO2009115364A1; WO2009095228A1; WO2017051145A3

Designated contracting state (EPC)  
AT BE CH DE DK ES FR GB IT LI NL SE

DOCDB simple family (publication)  
**EP 0740039 A1 19961030**; **EP 0740039 B1 19991103**; AT E186366 T1 19991115; DE 19616271 A1 19961031; DE 19616271 C2 20011004; DE 19616271 C5 20080417; DE 59603530 D1 19991209; DK 0740039 T3 20000117; ES 2140738 T3 20000301; PL 179949 B1 20001130; PL 313994 A1 19961112

DOCDB simple family (application)  
**EP 96103862 A 19960312**; AT 96103862 T 19960312; DE 19616271 A 19960424; DE 59603530 T 19960312; DK 96103862 T 19960312; ES 96103862 T 19960312; PL 31399496 A 19960426