

Title (en)  
GUIDE SYSTEM FOR CONTINUOUSLY CAST METAL

Title (de)  
STRANGFÜHRUNGSGERÜST

Title (fr)  
CADRE DE GUIDAGE POUR METAL COULE EN CONTINU

Publication  
**EP 0741618 A1 19961113 (DE)**

Application  
**EP 95906267 A 19950119**

Priority  
• DE 9500093 W 19950119  
• DE 4403047 A 19940128

Abstract (en)  
[origin: US6070648A] PCT No. PCT/DE95/00093 Sec. 371 Date Jul. 29, 1996 Sec. 102(e) Date Jul. 29, 1996 PCT Filed Jan. 20, 1995 PCT Pub. No. WO95/20446 PCT Pub. Date Aug. 3, 1995 Molten metal is poured into a continuous casting mold having a rectangular mold exit opening to produce a rectangular metal strand having a liquid core, a width and a thickness. A convex shape is imparted to the rectangular strand along at least a part of the width thereof downstream of the casting mold by arranging a plurality of oppositely disposed guide rolls immediately downstream of the rectangular mold exit opening so that the cast strand while travelling from the mold exit opening through the plurality of guide rolls expands along at least part of its width no more than 8% of the strand thickness, thereby preventing snaking of the strand.

IPC 1-7  
**B22D 11/128**

IPC 8 full level  
**B22D 11/00** (2006.01); **B22D 11/128** (2006.01)

CPC (source: EP US)  
**B22D 11/1287** (2013.01 - EP US)

Citation (search report)  
See references of WO 9520446A1

Designated contracting state (EPC)  
AT BE DE ES FR GB IT

DOCDB simple family (publication)  
**US 6070648 A 20000606**; AT E196106 T1 20000915; AU 1453395 A 19950815; CA 2182020 A1 19950803; CN 1064871 C 20010425; CN 1139895 A 19970108; DE 4403047 C1 19950810; DE 59508704 D1 20001012; EP 0741618 A1 19961113; EP 0741618 B1 20000906; ES 2149343 T3 20001101; JP 3069375 B2 20000724; JP H09508069 A 19970819; WO 9520446 A1 19950803; ZA 95674 B 19960207

DOCDB simple family (application)  
**US 68266996 A 19960729**; AT 95906267 T 19950119; AU 1453395 A 19950119; CA 2182020 A 19950119; CN 95191380 A 19950119; DE 4403047 A 19940128; DE 59508704 T 19950119; DE 9500093 W 19950119; EP 95906267 A 19950119; ES 95906267 T 19950119; JP 51982195 A 19950119; ZA 95674 A 19950127