

Title (en)

Process for guiding rectangular strands in a guide system

Title (de)

Verfahren zur Führung von Rechtecksträngen in einem Strangführungsgerüst

Title (fr)

Procédé de guidage de lingots continus à section rectangulaire dans un cadre de guidage

Publication

**EP 0741619 B1 20000927 (DE)**

Application

**EP 95906270 A 19950119**

Priority

- DE 9500096 W 19950119
- DE 4403046 A 19940128

Abstract (en)

[origin: US6070646A] PCT No. PCT/DE95/00096 Sec. 371 Date Jul. 29, 1996 Sec. 102(e) Date Jul. 29, 1996 PCT Filed Jan. 19, 1995 PCT Pub. No. WO95/20447 PCT Pub. Date Aug. 3, 1995A continuous casting device comprises, in combination, a continuous casting mold for receiving molten metal, and at least one pair of guide rolls disposed immediately downstream of the mold exit opening. The exit opening of the mold is rectangular shaped so as to permit a rectangular strand to be cast which has a liquid core, a width and a thickness. The guide rolls are constructed so as to impart to the rectangular strand leaving the mold exit opening a convex shape so as to prevent snaking of the strand within the continuous casting device. The convexity concavity extends along at least a part of the width of the strand and is no more than 8% of the strand thickness.

IPC 1-7

**B22D 11/128**

IPC 8 full level

**B22D 11/128** (2006.01)

CPC (source: EP US)

**B22D 11/1287** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE DE ES FR GB IT

DOCDB simple family (publication)

**US 6070646 A 20000606**; AT E196617 T1 20001015; AU 1453695 A 19950815; CA 2182021 A1 19950803; CN 1057241 C 20001011; CN 1139894 A 19970108; DE 4403046 C1 19950817; DE 59508759 D1 20001102; EP 0741619 A1 19961113; EP 0741619 B1 20000927; ES 2149965 T3 20001116; JP 2994757 B2 19991227; JP H09508071 A 19970819; WO 9520447 A1 19950803; ZA 95675 B 19960207

DOCDB simple family (application)

**US 68266896 A 19960729**; AT 95906270 T 19950119; AU 1453695 A 19950119; CA 2182021 A 19950119; CN 95191378 A 19950119; DE 4403046 A 19940128; DE 59508759 T 19950119; DE 9500096 W 19950119; EP 95906270 A 19950119; ES 95906270 T 19950119; JP 51982495 A 19950119; ZA 95675 A 19950127