

Title (en)  
HYDRAULIC FLUID LEAK DETECTION SYSTEM AND METHOD

Title (de)  
HYDRAULISCHES LECKANZEIGESYSTEM BEI FLÜSSIGKEITEN UND VERFAHREN

Title (fr)  
SYSTEME ET PROCEDE DE DETECTION DE FUITE DE FLUIDES HYDRAULIQUES

Publication  
**EP 0741895 A4 19990120 (EN)**

Application  
**EP 95909425 A 19950201**

Priority  
• US 9501321 W 19950201  
• US 19151894 A 19940203  
• US 32892994 A 19941025

Abstract (en)  
[origin: US5703569A] Provided is a self-calibrating system which self-calibrates for operation regardless of the particular reservoir or expansion tank, which further detects when a hydraulic fluid system adapted to a turf care machine has developed a leak and which warns the machine operator of such a leak before an appreciable amount of hydraulic fluid is allowed to leak from the system. The system includes a reservoir for holding a quantity of hydraulic fluid. The reservoir is connected via a connecting tube or hose located at the upper-most portion of the reservoir and connected to an expansion tank mounted substantially adjacent to the reservoir. The expansion tank includes a fitting having an elongated tube extending down into the expansion tank. The end of this tube is maintained substantially below the level of hydraulic fluid in the expansion tank during operation of the turf care machine to which it is attached. As the machine is operated, the hydraulic fluid expands with rising temperatures, and the connecting tube communicates the expanding fluid to the expansion tank. When operation of the machine is discontinued the hydraulic fluid contracts as it cools. As the hydraulic fluid contracts, the hydraulic fluid in the expansion tank is automatically drawn by a siphoning action through the elongated tube within the expansion tank through the connecting tube and back into the reservoir. The self-calibrating leak detection system is adaptable to a variety of self propelled machines having hydraulically actuated devices. In particular, significant savings could be gained by the early detection of hydraulic system leaks on large, earth-moving equipment and the like. Further, the self-calibrating hydraulic fluid leak detection system may be retrofit onto existing hydraulic systems by the addition of an expansion tank to the hydraulic system reservoir.

IPC 1-7  
**G08B 21/00**

IPC 8 full level  
**A01D 69/02** (2006.01); **A01D 75/30** (2006.01); **G01F 23/72** (2006.01); **G01F 23/74** (2006.01); **G01F 25/00** (2006.01); **G01M 3/32** (2006.01)

CPC (source: EP US)  
**A01D 69/03** (2013.01 - EP US); **G01F 23/72** (2013.01 - EP US); **G01F 23/74** (2013.01 - EP US); **G01F 25/20** (2022.01 - EP US); **G01M 3/3245** (2013.01 - EP US)

Citation (search report)  
• [Y] US 4781057 A 19881101 - HYFANTIS JR GEORGE J [US], et al  
• [Y] WO 8804031 A1 19880602 - NDE TECHNOLOGY INC [US]  
• [A] US 4807464 A 19890228 - JANOTTA LOUIS J [US]  
• [A] US 5254976 A 19931019 - SCHUELER ROBERT A [US]  
• [AP] US 5319572 A 19940607 - WILHELM PETER L [US], et al  
• [A] PATENT ABSTRACTS OF JAPAN vol. 011, no. 016 (M - 554) 16 January 1987 (1987-01-16)  
• See references of WO 9521432A1

Designated contracting state (EPC)  
DE FR GB

DOCDB simple family (publication)  
**US 5703569 A 19971230**; AU 1739295 A 19950821; DE 69528965 D1 20030109; EP 0741895 A1 19961113; EP 0741895 A4 19990120; EP 0741895 B1 20021127; WO 9521432 A1 19950810

DOCDB simple family (application)  
**US 48191095 A 19950607**; AU 1739295 A 19950201; DE 69528965 T 19950201; EP 95909425 A 19950201; US 9501321 W 19950201