

Title (en)

Straight-line capping machine and capping method

Title (de)

Kapselmaschine des geradlinigen Types sowie Kapselmaschine

Title (fr)

Machine d'encapsulage du type rectiligne et procédé d'encapsulage

Publication

EP 0749937 B1 20020911 (EN)

Application

EP 96304471 A 19960617

Priority

- US 49139895 A 19950619
- US 63352396 A 19960417
- US 63341696 A 19960417

Abstract (en)

[origin: EP0749937A2] A straight line capping machine (1) is provided that wherein the cap tightening discs (75-78) and the container grasping mechanism (49) are synchronized to a predetermined relationship so as to prevent cocked caps, loose caps and/or scuffed caps. In particular, the mechanisms are synchronized to ensure that the tangential velocity of the rear cap tightening disc minus the tangential velocity of the front cap tightening disc is about twice the predetermined velocity of the container passing through the capping machine.

IPC 1-7

B67B 3/20; **B65B 7/28**

IPC 8 full level

B65B 7/28 (2006.01); **B67B 3/20** (2006.01); **B67B 3/26** (2006.01)

CPC (source: EP)

B65B 7/2835 (2013.01); **B67B 3/2046** (2013.01); **B67B 3/26** (2013.01)

Cited by

ES2147690A2; CN108622834A; CN112874846A; CN115140693A

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0749937 A2 19961227; **EP 0749937 A3 19970319**; **EP 0749937 B1 20020911**; AT E223865 T1 20020915; DE 69623541 D1 20021017; DE 69623541 T2 20030109; ES 2181851 T3 20030301

DOCDB simple family (application)

EP 96304471 A 19960617; AT 96304471 T 19960617; DE 69623541 T 19960617; ES 96304471 T 19960617