

Title (en)

Ferritic steel and its manufacture and use

Title (de)

Ferritischer Stahl und Verfahren zu seiner Herstellung und Verwendung

Title (fr)

Acier ferritique; sa fabrication et son utilisation

Publication

EP 0750049 A1 19961227 (DE)

Application

EP 96107884 A 19960517

Priority

- DE 19521836 A 19950616
- DE 19605696 A 19960216

Abstract (en)

A ferritic steel contains (wt. %) 0.05-0.3 C, 0.8-3.0 Mn, 0.4-2.5 Al, < 0.2 Si, < 0.08 P, < 0.05 S, balance Fe and unavoidable impurities. Ceq = %C + <1>/20%Mn + <1>/20%Cr + <1>/15%Mo = 0.1-0.325. Al ≥ 7.6Ce_q - 0.36 wt. %. Also claimed is a process for producing the above steel having high strength, good cold workability and surface quality in the hot-rolled state and good cold-rollability with a structure consisting predominantly of pre-eutectic ferrite and smaller proportions of martensite and/or bainite and/or residual austenite, which is cast into a blank, hot rolled with a starting temperature of above 1000 degrees C and an end temperature (ET) in the region Ar3 - 50 degrees C < ET < Ar3 + 100 degrees C, cooled from the ET at a rate of 15-70 K/s to the coiling temperature which is below 500 degrees C, and coiled.

Abstract (de)

Die Erfindung betrifft einen Dualphasenstahl mit überwiegend polygonal-ferritischem Gefüge, in dem eine kohlenstoffangereicherte perlitfreie harte zweite Phase eingelagert ist, die aus Martensit und/oder Bainit und/oder Restaustenit besteht, mit hoher Festigkeit und guter Umformbarkeit sowie verbesserter Oberflächenqualität nach einer Warmverformung, ein Verfahren zu seiner Herstellung und Verwendung. <IMAGE>

IPC 1-7

C21D 8/02; C22C 38/06

IPC 8 full level

C21D 8/02 (2006.01); **C22C 38/04** (2006.01); **C22C 38/06** (2006.01)

CPC (source: EP)

C21D 8/0226 (2013.01); **C22C 38/04** (2013.01); **C22C 38/06** (2013.01); **C21D 2211/001** (2013.01); **C21D 2211/002** (2013.01);
C21D 2211/005 (2013.01); **C21D 2211/008** (2013.01)

Citation (applicant)

- DE 2924340 C2 19851017
- EP 0072867 B1 19860416
- DE 3440752 C2 19870806

Citation (search report)

- [X] BE 899253 A 19840716 - GIELEN PAUL M E L
- [A] FR 2253841 A1 19750704 - CENTRO SPERIMENT METALLURG [IT]
- [A] US 4316753 A 19820223 - KANEKO KUNISHIGE, et al
- [A] EP 0586704 A1 19940316 - NIPPON STEEL CORP [JP]
- [PX] US 5470529 A 19951128 - NOMURA SHIGEKI [JP], et al
- [X] PATENT ABSTRACTS OF JAPAN vol. 018, no. 668 (C - 1289) 16 December 1994 (1994-12-16)
- [X] PATENT ABSTRACTS OF JAPAN vol. 017, no. 373 (C - 1083) 14 July 1993 (1993-07-14)

Cited by

AU756917B2; CN110551878A; DE10327383C5; EP1642990A4; NL1007739C2; CZ298363B6; AT525283A4; AT525283B1; US6616778B1;
US6773522B1; WO9929444A1; US7922835B2; US8262818B2; EP1633894B1

Designated contracting state (EPC)

AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0750049 A1 19961227; AR 002501 A1 19980325; BR 9608672 A 19990504; CA 2224817 A1 19970103; CN 1190997 A 19980819;
CZ 402497 A3 19980617; HU P9801908 A2 19981130; HU P9801908 A3 19981228; MX 9710230 A 19980329; PL 324555 A1 19980608;
TR 199701720 T1 19980521; WO 9700332 A1 19970103

DOCDB simple family (application)

EP 96107884 A 19960517; AR 10318196 A 19960614; BR 9608672 A 19960601; CA 2224817 A 19960601; CN 96195583 A 19960601;
CZ 402497 A 19960601; EP 9602383 W 19960601; HU P9801908 A 19960601; MX 9710230 A 19960601; PL 32455596 A 19960601;
TR 9701720 T 19960601