

Title (en)

Method and device for making recesses in asphalt layers

Title (de)

Verfahren und Vorrichtung zum Herstellen von Aussparungen in Asphaltschichten

Title (fr)

Procédé et dispositif pour la fabrication d'évidements dans des couches d'asphalte

Publication

EP 0751259 B1 20010816 (DE)

Application

EP 96107626 A 19960514

Priority

DE 19523503 A 19950628

Abstract (en)

[origin: EP0751259A1] When an asphalt layer is laid or shortly after it has been laid, a frame (1) is worked into the location of an intended recess (2) in the asphalt layer (3). The frame has the shape of the intended recess. The still warm asphalt located inside the frame is sucked away by a suction device. The recesses in the upper asphalt layer are produced in a grid formation, which corresponds to the distance between rail sleepers to be fixed on the asphalt layer or to a whole number multiple of such distance. The recesses are produced in the centre between the intended run of the two rails of the track and are provided for the accommodation of an anchoring projection extending downwards from the sleepers.

IPC 1-7

E01B 37/00; **E01B 29/06**

IPC 8 full level

E01B 29/06 (2006.01); **E01B 37/00** (2006.01)

CPC (source: EP)

E01B 29/06 (2013.01); **E01B 37/00** (2013.01)

Cited by

CN111335234A

Designated contracting state (EPC)

AT BE CH DE ES FR IT LI LU NL

DOCDB simple family (publication)

EP 0751259 A1 19970102; **EP 0751259 B1 20010816**; AT E204350 T1 20010915; DE 19523503 A1 19970102; DE 59607486 D1 20010920; ES 2171204 T3 20020901

DOCDB simple family (application)

EP 96107626 A 19960514; AT 96107626 T 19960514; DE 19523503 A 19950628; DE 59607486 T 19960514; ES 96107626 T 19960514