

Title (en)

Stranding station for alternate or SZ stranding machine

Title (de)

Verseilanlage für reversierenden oder SZ Verseilmaschine

Title (fr)

Station de câblage pour machine de câblage alterné ou de type SZ

Publication

**EP 0756290 B1 19991006 (FR)**

Application

**EP 96111416 A 19960716**

Priority

FR 9509089 A 19950726

Abstract (en)

[origin: EP0756290A1] Individual strands pass through equally spaced peripheral holes (opt., notches) in a stationary guide-plate (34), a succession of transitional disks (50) and a motor-driven (M) laying-up disk (38), before combining as cable at the draw-plate (FC) for finishing treatments. Transition disks are coupled to a shaft (54), connected to the driven disk (38), running in a guide-plate bearing (58), by friction clutch-plates (60) fixed on the shaft. The shaft is opt. hollow to feed in any core component. Clutch pressure is derived from strand tensions, frictionally transmitted from the peripheral holes, or from springs. By adjusting friction surface areas, or spring pressures, torque transmitted to the disks steadily increases as the driven disk is approached.

IPC 1-7

**H01B 13/02**

IPC 8 full level

**H01B 13/02** (2006.01)

CPC (source: EP US)

**H01B 13/0257** (2013.01 - EP US)

Cited by

CN101934444A

Designated contracting state (EPC)

AT CH DE FI IT LI

DOCDB simple family (publication)

**EP 0756290 A1 19970129; EP 0756290 B1 19991006;** AT E185440 T1 19991015; DE 69604543 D1 19991111; DE 69604543 T2 20000511; FR 2737337 A1 19970131; FR 2737337 B1 19970919; US 5699660 A 19971223

DOCDB simple family (application)

**EP 96111416 A 19960716;** AT 96111416 T 19960716; DE 69604543 T 19960716; FR 9509089 A 19950726; US 68343796 A 19960719