

Title (en)
SELF-LOCKING ABSEIL DEVICE

Title (de)
SELBSTBLOCKIERENDE ABSEILVORRICHTUNG

Title (fr)
DESCENDEUR AUTOBLOQUANT

Publication
EP 0757580 A1 19970212 (FR)

Application
EP 95918642 A 19950426

Priority
• FR 9500543 W 19950426
• FR 9405331 A 19940427

Abstract (en)
[origin: WO9528990A1] An abseil device including an integral main body (1) with two generally parallel main flanges (3, 4) joined together via a longitudinal connecting flange (6) and provided with two apertures (13, 14) engaged by a hook ring (2). The apertures (13, 14) include slanted edges (12) along which the hook ring (2) is slidable for wedging an intermediate portion (17) of a rope (5) and thereby locking the abseil device thereon. The device can be released by pivoting the main body (1). A self-locking abseil device suitable for mountaineering, caving, rock climbing or work in places high above the ground is thus provided.

IPC 1-7
A62B 1/14; **A62B 35/04**

IPC 8 full level
A62B 1/14 (2006.01); **A62B 1/04** (2006.01); **A62B 35/04** (2006.01); **A63B 29/02** (2006.01)

CPC (source: EP US)
A62B 1/04 (2013.01 - EP US); **A62B 35/04** (2013.01 - EP US); **A63B 29/02** (2013.01 - EP US)

Citation (search report)
See references of WO 9528990A1

Designated contracting state (EPC)
AT BE CH DE ES FR GB IT LI

DOCDB simple family (publication)
WO 9528990 A1 19951102; AT E195662 T1 20000915; DE 69518514 D1 20000928; EP 0757580 A1 19970212; EP 0757580 B1 20000823; FR 2719227 A1 19951103; FR 2719227 B1 19960607; JP H10510723 A 19981020; US 5850890 A 19981222

DOCDB simple family (application)
FR 9500543 W 19950426; AT 95918642 T 19950426; DE 69518514 T 19950426; EP 95918642 A 19950426; FR 9405331 A 19940427; JP 52741595 A 19950426; US 73224996 A 19961021