

Title (en)
PRESSER APPARATUS

Title (de)
PRESSANLAGE

Title (fr)
DISPOSITIF PRESSEUR

Publication
EP 0760742 A1 19970312 (EN)

Application
EP 95919552 A 19950524

Priority
• EP 95919552 A 19950524
• EP 94303919 A 19940531
• GB 9501183 W 19950524

Abstract (en)
[origin: WO9532858A1] During the formation of a container (C) from a blank, a pair of opposite end tabs of the partially erected container travelling on a conveyor (2) are closed against side walls at the front and rear of the container in the direction of travel by presser devices (18, 20) travelling with the container on their own conveying means (14a, 14b). The front and rear presser devices (18, 20) are mounted on separate units of the conveying means. The respective units can be driven at different speeds and are controlled so as to open the spacing between the presser devices at entry to and exit from the conveyor path and to close said spacing between said entry and exit to clamp the container tabs against said side walls.

IPC 1-7
B31B 5/74

IPC 8 full level
B31B 1/74 (2006.01); **B31B 5/74** (2006.01)

CPC (source: EP US)
B31B 50/00 (2017.07 - EP); **B31B 50/784** (2017.07 - EP US); **B31B 50/0044** (2017.07 - EP); **B31B 50/60** (2017.07 - EP);
B31B 2100/00 (2017.07 - EP); **B31B 2120/30** (2017.07 - EP)

Citation (search report)
See references of WO 9532858A1

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IE IT LI NL PT SE

DOCDB simple family (publication)
WO 9532858 A1 19951207; AU 2533695 A 19951221; CA 2187183 A1 19951207; CN 1149274 A 19970507; EP 0760742 A1 19970312;
HU 9602808 D0 19961128; JP 2000510774 A 20000822; PL 318469 A1 19970623; TR 28494 A 19960902; ZA 954195 B 19961125

DOCDB simple family (application)
GB 9501183 W 19950524; AU 2533695 A 19950524; CA 2187183 A 19950524; CN 95193351 A 19950524; EP 95919552 A 19950524;
HU 9602808 A 19950524; JP 50048196 A 19950524; PL 31846995 A 19950524; TR 62995 A 19950529; ZA 954195 A 19950523