

Title (en)
HEAD GASKET

Title (de)
ZYLINDERDICHTUNGSRING

Title (fr)
JOINT DE CULASSE DE CYLINDRE

Publication
EP 0760902 A1 19970312 (EN)

Application
EP 95918228 A 19950424

Priority
• SE 9500443 W 19950424
• SE 9401401 A 19940425

Abstract (en)
[origin: WO9529333A1] The present invention relates to a cylinder head gasket for internal combustion engines. According to the invention, the gasket comprises a laminate which consists in a thin stainless steel plate or a heat-resistant steel plate that is coated on each side with still thinner carrier-calendared rubber films which have a thickness of at least 0.05 mm and which are affixed to the steel plate by vulcanization. The steel plate suitably has a thickness of about 0.2 to 0.4 mm and the rubber films each have a thickness of at least 0.05 to 0.20 mm.

IPC 1-7
F02F 11/00

IPC 8 full level
F02F 11/00 (2006.01)

CPC (source: EP)
F02F 11/002 (2013.01)

Citation (search report)
See references of WO 9529333A1

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
WO 9529333 A1 19951102; AT E178121 T1 19990415; AU 2422495 A 19951116; CA 2186629 A1 19951102; CA 2186629 C 20030617;
CZ 286582 B6 20000517; CZ 302296 A3 19970212; DE 69508578 D1 19990429; DE 69508578 T2 19990715; DK 0760902 T3 20030414;
EP 0760902 A1 19970312; EP 0760902 B1 19990324; ES 2129821 T3 19990616; GR 3029793 T3 19990630; HU 218781 B 20001228;
HU 9602939 D0 19961230; HU 777502 A 19980528; SE 502513 C2 19951106; SE 9401401 D0 19940425; SE 9401401 L 19951026

DOCDB simple family (application)
SE 9500443 W 19950424; AT 95918228 T 19950424; AU 2422495 A 19950424; CA 2186629 A 19950424; CZ 302296 A 19950424;
DE 69508578 T 19950424; DK 95918228 T 19950424; EP 95918228 A 19950424; ES 95918228 T 19950424; GR 990400594 T 19990325;
HU 9602939 A 19950424; SE 9401401 A 19940425