

Title (en)

Beer barrel stopper provided with an ejection preventing means

Title (de)

Bierfassverschluss mit Einrichtung zum Verhindern des Herausschleudern des Verschlusses

Title (fr)

Fermeture de tonneau à bière avec dispositif pour empêcher l'éjection de la fermeture

Publication

EP 0761555 A1 19970312 (EN)

Application

EP 96300230 A 19960111

Priority

JP 25446695 A 19950907

Abstract (en)

A spear-tube stopper for use with pressurisable beer barrels, having an ejection preventing member. The ejection preventing member having a portion protruding from a window of the body of the stopper and having a length sufficient to engage the lower edge part of the barrel cap to prevent removal of the stopper from the barrel but being retractable by inserting a gas bulb/dispenser connecting means sufficiently into the stopper. The ejection preventing member including a hanging piece, made of stainless steel with a high elasticity modulus, whose upper part is fixed onto the upper end part of a down-tube, providing an inverted U-shaped notch onto a part of said dangling piece and bending the upper part of the notch outward like an arc to form said protruding portion. <IMAGE>

IPC 1-7

B65D 39/00

IPC 8 full level

B67D 1/08 (2006.01)

CPC (source: EP)

B67D 1/0838 (2013.01)

Citation (search report)

[X] JP H07232799 A 19950905 - TOA SEIKI CO LTD

Cited by

GB2331294A; EP0801025A1; US5833098A; US7546935B2; WO03093163A1

Designated contracting state (EPC)

BE DE DK GB

DOCDB simple family (publication)

EP 0761555 A1 19970312

DOCDB simple family (application)

EP 96300230 A 19960111