

Title (en)

Device for bridging expansion joints, particularly in bridges or roads

Title (de)

Vorrichtung zur Überbrückung von Dehnfugen, insbesondere in Brücken oder Fahrbahnen

Title (fr)

Dispositif de pontage pour joints de dilatation, en particulier dans des ponts ou dans des chaussées

Publication

**EP 0761887 B1 19980715 (DE)**

Application

**EP 95116990 A 19951027**

Priority

DE 19532750 A 19950905

Abstract (en)

[origin: EP0761887A1] The elastic sealing strip extending over the seam deflects downwards at the middle as the joint edges move together. Lengthwise beads on the strip edges are secured in chambers (40), having edge strips folded back against them. At the underside each chamber is enclosed by a surface (39) sloping upwards towards the seam (F) and ending at a V-shaped edge (35) fitting in a mating notch (13) in the underside of the bead (6). The folded-over bead edge strip (8) presses against the flat top surface (37) of the chamber, whose bottom surface can likewise be flat, while the angle of the edge can be 90 deg. The top surface (11) of the bead can be parallel to that of the chamber in the installed position, while the top and bottom surfaces (9,10) of the edge strip are flat and parallel. A wedge (20), tapering away from the seam, is inserted between the bead and edge strip at the edge.

IPC 1-7

**E01D 19/06; E01C 11/12**

IPC 8 full level

**E01C 11/12** (2006.01); **E01D 19/06** (2006.01)

CPC (source: EP)

**E01D 19/06** (2013.01)

Designated contracting state (EPC)

AT CH DE FR GB LI

DOCDB simple family (publication)

**EP 0761887 A1 19970312; EP 0761887 B1 19980715**; AT E168429 T1 19980815; DE 19532750 C1 19961017; DE 59502840 D1 19980820

DOCDB simple family (application)

**EP 95116990 A 19951027**; AT 95116990 T 19951027; DE 19532750 A 19950905; DE 59502840 T 19951027