

Title (en)
HIGH-PRESSURE CLEANING APPLIANCE WITH SAFETY INSULATION

Title (de)
HOCHDRUCKREINIGUNGSGERÄT MIT SICHERHEITSISOLIERUNG

Title (fr)
APPAREIL DE NETTOYAGE SOUS HAUTE PRESSION A ISOLATION DE SECURITE

Publication
EP 0764059 A1 19970326 (DE)

Application
EP 94928358 A 19940915

Priority
• DE 4421330 A 19940617
• EP 9403086 W 19940915

Abstract (en)
[origin: WO9535171A1] A high-pressure cleaning appliance has an electric motor arranged in a housing, a high-pressure pump arranged in a housing with at least one piston that enters a sealed pumping chamber and a swash plate carried on a motor shaft that extends out of the housing of the electric motor. The pistons of the high-pressure pump are elastically supported on the swash plate. In order to electrically insulate the area of the swash plate drive, the transition through the swash plate from the motor shaft to the pistons is electrically interrupted by an intermediate layer of electrically insulating material.

IPC 1-7
B08B 3/02; **F04B 1/14**

IPC 8 full level
A47L 9/28 (2006.01); **B08B 3/02** (2006.01); **F04B 1/14** (2006.01); **F04B 17/03** (2006.01)

CPC (source: EP US)
B08B 3/026 (2013.01 - EP US); **F04B 1/146** (2013.01 - EP US); **F04B 17/03** (2013.01 - EP US); **F05C 2253/12** (2013.01 - EP US)

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
WO 9535171 A1 19951228; AT E173961 T1 19981215; CA 2191967 C 20000321; DE 59407409 D1 19990114; DE 9421814 U1 19961024; DK 0764059 T3 19990816; EP 0764059 A1 19970326; EP 0764059 B1 19981202; JP 2846476 B2 19990113; JP H09509602 A 19970930; US 5886436 A 19990323

DOCDB simple family (application)
EP 9403086 W 19940915; AT 94928358 T 19940915; CA 2191967 A 19940915; DE 59407409 T 19940915; DE 9421814 U 19940915; DK 94928358 T 19940915; EP 94928358 A 19940915; JP 50151796 A 19940915; US 76772896 A 19961216