

Title (en)
VARIOUS RECORDING/REPRODUCTION MODES IN RECORDING/REPRODUCING A DIGITAL INFORMATION SIGNAL AND AT LEAST ONE DIGITAL AUXILIARY SIGNAL

Title (de)
VERSCHIEDENE AUFZEICHNUNGS-/WIEDERGABEMODI FÜR DIE AUFZEICHNUNG/WIEDERGABE EINES DIGITALEN INFORMATIONSSIGNALS UND MINDESTENS EINES DIGITALEN HILFSSIGNALS

Title (fr)
DIVERS MODES D'ENREGISTREMENT ET DE REPRODUCTION POUR L'ENREGISTREMENT ET LA REPRODUCTION D'UN SIGNAL D'INFORMATION NUMERIQUE ET D'AU MOINS UN SIGNAL AUXILIAIRE NUMERIQUE

Publication
EP 0764326 A2 19970326 (EN)

Application
EP 96904220 A 19960313

Priority

- EP 96904220 A 19960313
- EP 95200847 A 19950404
- IB 9600208 W 19960313

Abstract (en)
[origin: WO9631879A2] An apparatus for recording a digital information signal in slant tracks on a longitudinal magnetic record carrier (10) is described. The apparatus is capable of recording a digital information signal and at least one digital auxiliary signal in a track. The apparatus comprises an input terminal (1) for receiving the digital information signal and an input terminal (2) for receiving the at least one digital auxiliary signal. Channel encoding means (6) are present for carrying out a channel encoding step on the digital information signal so as to obtain a channel encoded digital information signal. Writing means (8) are present for writing the channel encoded digital information signal and the digital auxiliary signal in a track. The apparatus is adapted to function in a first recording mode in which said channel encoded digital information signal is recorded in a first track portion (TP1) of the tracks and a second recording mode in which the apparatus is adapted to record the channel encoded digital information signal in a second track portion (TP2) of the tracks and the at least one digital auxiliary signal in a third track portion (TP3) in the tracks. The second and third track portions lie within said first track portions (TP1). More specifically, the second and third track portion in the track are separated by an edit gap (G4), and the total length of the second and third track portion and the edit gap equals the length (L1) of the first track portion.

IPC 1-7
G11B 20/12; H04N 5/7826; H04N 9/80

IPC 8 full level
G11B 15/087 (2006.01); **G11B 20/12** (2006.01); **G11B 20/14** (2006.01); **G11B 27/036** (2006.01); **G11B 27/10** (2006.01); **G11B 27/30** (2006.01); **H04N 5/7826** (2006.01); **H04N 5/92** (2006.01); **H04N 9/80** (2006.01); **H04N 9/82** (2006.01); **G11B 27/032** (2006.01)

CPC (source: EP)
G11B 15/087 (2013.01); **G11B 20/1207** (2013.01); **G11B 20/1426** (2013.01); **G11B 27/036** (2013.01); **G11B 27/107** (2013.01); **G11B 27/3027** (2013.01); **G11B 27/3063** (2013.01); **H04N 9/8216** (2013.01); **G11B 27/032** (2013.01); **G11B 2220/90** (2013.01); **H04N 5/78263** (2013.01)

Citation (search report)
See references of WO 9631879A2

Designated contracting state (EPC)
AT DE ES FR GB IT PT

DOCDB simple family (publication)
WO 9631879 A2 19961010; **WO 9631879 A3 19970103**; CN 1158177 A 19970827; EP 0764326 A2 19970326; JP H10501947 A 19980217; TW 412731 B 20001121

DOCDB simple family (application)
IB 9600208 W 19960313; CN 96190496 A 19960313; EP 96904220 A 19960313; JP 53013796 A 19960313; TW 85103360 A 19960320