

Title (en)

Method for manufacturing a fluid cavity in an ink jet print head

Title (de)

Verfahren zum Herstellen eines Flüssigkeitshohlraumes in einem Tintenstrahldruckkopf

Title (fr)

Procédé de fabrication d'une cavité à fluide dans une tête d'impression à jet d'encre

Publication

**EP 0764534 A3 19970917 (EN)**

Application

**EP 96306775 A 19960918**

Priority

US 53086795 A 19950919

Abstract (en)

[origin: EP0764534A2] A continuous ink jet printing system includes a resonator having an internal fluid cavity. An initial aperture is drilled through the internal fluid cavity. A wire electrical discharge machining process is then applied to the surface of the internal fluid cavity to achieve a desired aperture dimension. The final aperture can be honed to improve surface finish. <IMAGE>

IPC 1-7

**B41J 2/16**

IPC 8 full level

**B41J 2/045** (2006.01); **B41J 2/025** (2006.01); **B41J 2/055** (2006.01); **B41J 2/16** (2006.01)

CPC (source: EP)

**B41J 2/025** (2013.01)

Citation (search report)

- [Y] EP 0299143 A1 19890118 - RAYCON TEXTRON INC [US]
- [A] US 4685185 A 19870811 - BOSO BRIAN [US], et al
- [A] US 4711981 A 19871208 - ASO TOSHIYUKI [JP], et al
- [A] US 5235746 A 19930817 - LEONARD MARC B [US]
- [A] US 4746929 A 19880524 - LIN LARRY W [US], et al
- [Y] PATENT ABSTRACTS OF JAPAN vol. 016, no. 135 (M - 1230) 6 April 1992 (1992-04-06)
- [XY] PATENT ABSTRACTS OF JAPAN vol. 009, no. 121 (M - 382) 25 May 1985 (1985-05-25)
- [A] PATENT ABSTRACTS OF JAPAN vol. 012, no. 206 (M - 708) 14 June 1988 (1988-06-14)
- [A] PATENT ABSTRACTS OF JAPAN vol. 018, no. 411 (M - 1648) 2 August 1994 (1994-08-02)
- [A] PATENT ABSTRACTS OF JAPAN vol. 013, no. 369 (M - 860) 16 August 1989 (1989-08-16)

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**EP 0764534 A2 19970326**; **EP 0764534 A3 19970917**; CA 2185838 A1 19970320; JP H09169116 A 19970630

DOCDB simple family (application)

**EP 96306775 A 19960918**; CA 2185838 A 19960918; JP 24805796 A 19960919