

Title (en)
Closure for teller machine

Title (de)
Verschlussklappenanordnung für die Zugriffsöffnung an einem Bankautomaten

Title (fr)
Fermeture pour machine bancaire

Publication
EP 0766210 A3 20000315 (DE)

Application
EP 96112531 A 19960802

Priority
DE 19536484 A 19950929

Abstract (en)
[origin: EP0766210A2] The cover has a part cylindrical flap (38) coupled via at least one lever (44) perpendicular to its pivot axis to a frame. The flap is rotated about the pivot axis via a reversible electric motor, with a cam element (56) mounted on its drive shaft cooperating with a cam follower (58) attached to the lever. The flap is spring biased into the closed position, with a closure hook (68) mounted on the drive shaft cooperating with a hook element (78) provided by the lever, to prevent forced opening of the flap.

IPC 1-7
G07F 7/10; **G07D 11/00**

IPC 8 full level
G07D 11/00 (2006.01); **G07F 7/10** (2006.01); **G07F 19/00** (2006.01)

CPC (source: EP)
G07F 19/20 (2013.01); **G07F 19/201** (2013.01); **G07F 19/205** (2013.01)

Citation (search report)

- [XA] US 5172643 A 19921222 - KOSHIDA YOSHINORI [JP], et al
- [A] US 4602724 A 19860729 - BOND KEVIN J [GB], et al
- [A] EP 0315735 A1 19890517 - IBM [US]
- [A] US 3957173 A 19760518 - ROUDEBUSH MELVIN T
- [A] US 4251009 A 19810217 - MCLAUGHLIN RICHARD S, et al

Cited by
WO2011161154A1; US8935884B2; EP2400470A1; WO2011015545A1

Designated contracting state (EPC)
CH DE FR GB IT LI PT SE

DOCDB simple family (publication)
EP 0766210 A2 19970402; **EP 0766210 A3 20000315**; **EP 0766210 B1 20021120**; DE 19536484 C1 19970403; DE 59609879 D1 20030102

DOCDB simple family (application)
EP 96112531 A 19960802; DE 19536484 A 19950929; DE 59609879 T 19960802