

Title (en)
CRYOCABLE

Title (de)
CRYOKABEL

Title (fr)
CRYOCABLE

Publication
EP 0766871 B1 19980506 (EN)

Application
EP 95915478 A 19950331

Priority
• US 9503993 W 19950331
• US 22797494 A 19940415

Abstract (en)
[origin: WO9528750A1] An electrical interconnect provides a path between cryogenic or cryocooled circuitry and ambient temperatures. As a system, a cryocable (10) is combined with a trough-line contact or transition (20). In the preferred embodiment, the cryocable (10) comprises a conductor (11) disposed adjacent an insulator (12) which is in turn disposed adjacent another conductor (13). The components are sized so as to balance heat load through the cryocable (10) with the insertion loss. In the most preferred embodiment, a coaxial cryocable (10) has a center conductor (11) surrounded by a dielectric (12) (e.g. Teflon<TM>) surrounded by an outer conductor (13) which has a thickness between about 6 and 20 microns. The heat load is preferably less than one Watt, and most preferably less than one tenth of a Watt, with an insertion loss less than one decibel. In another aspect of the invention, a trough-line contact or transition (20) is provided in which the center conductor (11) is partially enveloped by dielectric (12) to form a relatively flat portion (28). The preferred overall geometry of the preferred embodiment of the cable is generally cylindrical, although other geometries are possible (e.g. stripline, microstrip, coplanar or slotline geometries).

IPC 1-7
H01R 4/68; **H01P 5/08**

IPC 8 full level
H01B 11/00 (2006.01); **H01B 12/02** (2006.01); **H01P 3/06** (2006.01); **H01P 5/08** (2006.01); **H01R 4/68** (2006.01)

CPC (source: EP)
H01P 5/085 (2013.01); **H01R 4/68** (2013.01)

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
WO 9528750 A1 19951026; AT E165937 T1 19980515; CA 2187788 A1 19951026; CA 2187788 C 20010102; DE 69502397 D1 19980610; DE 69502397 T2 19981217; EP 0766871 A1 19970409; EP 0766871 B1 19980506; JP 3069130 B2 20000724; JP H09512130 A 19971202

DOCDB simple family (application)
US 9503993 W 19950331; AT 95915478 T 19950331; CA 2187788 A 19950331; DE 69502397 T 19950331; EP 95915478 A 19950331; JP 52698695 A 19950331