

Title (en)
Printing press

Title (de)
Druckmaschine

Title (fr)
Machine à imprimer

Publication
EP 0767058 A3 19980610 (EN)

Application
EP 96250217 A 19961002

Priority
US 53842295 A 19951002

Abstract (en)
[origin: EP0767058A2] A retractable in-line inking/coating apparatus can apply either spot or overall inking/coating material to a plate and/or a blanket on the first printing unit or on any consecutive printing unit of any rotary offset printing press. The inking/coating apparatus is pivotally mounted within the conventional dampener space of any lithographic printing unit. The aqueous component of the flexographic printing ink or aqueous coating material is evaporated and dried by high velocity, hot air dryers and high performance heat and moisture extractors so that the aqueous or flexographic ink or coating material on a freshly printed or coated sheet is dry and can be dry-trapped on the next printing unit. The inking/coating apparatus includes dual cradles that support first and second applicator rollers so that the inking/coating apparatus can apply a double bump of aqueous/flexographic or UV-curable printing ink or coating material to a plate on the plate cylinder, while simultaneously applying aqueous, flexographic or UV-curable printing ink or coating material to a plate or a blanket on the blanket cylinder, and thereafter onto a sheet as the sheet is transferred through the nip between the blanket cylinder and the impression cylinder. A triple bump is printed or coated on the last printing unit with the aid of an impression cylinder inking/coating unit. <IMAGE>

IPC 1-7
B41F 31/30; **B41F 23/08**

IPC 8 full level
B41F 23/04 (2006.01); **B41F 5/24** (2006.01); **B41F 11/00** (2006.01); **B41F 23/08** (2006.01); **B41F 31/08** (2006.01)

CPC (source: EP)
B41F 23/08 (2013.01); **B41P 2200/12** (2013.01)

Citation (search report)

- [DA] US 4615293 A 19861007 - JAHN HANS-GEORG [DE]
- [DA] US 5107790 A 19920428 - SLIKER LARRY J [US], et al
- [A] DE 4311834 A1 19941013 - ROLAND MAN DRUCKMASCH [DE]

Cited by
EP1754605A3; AU731488B2; DE19734100C5; DE19729977C2; DE19729985C2; CN103802446A; US6971310B1; US7055433B1; WO0108886A3; WO9901282A1

Designated contracting state (EPC)
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 0767058 A2 19970409; **EP 0767058 A3 19980610**; JP H09136398 A 19970527

DOCDB simple family (application)
EP 96250217 A 19961002; JP 28142096 A 19961002