

Publication

EP 0767272 A3 19970507

Application

EP 96111142 A 19960711

Priority

DE 19537173 A 19951006

Abstract (en)

[origin: DE19537173C1] The device has a cutting unit (19) with at least one severing element (41). This is flexible in itself, or is mounted on a flexible carrier element (33). This is rotated to move the severing element from an inactive into a working position, in which it cuts the insertion strip coming from the guide plate. A weight (45) is fastened to the other end of the severing element. A holder or guide unit acts with the guide plate, and several cutting units are distributed across the width of the unit.

IPC 1-7

D21G 9/00; **D21F 7/04**

IPC 8 full level

B26D 1/28 (2006.01); **B26D 1/547** (2006.01); **B26D 7/26** (2006.01); **D21F 7/04** (2006.01); **D21G 9/00** (2006.01)

CPC (source: EP US)

B26D 1/285 (2013.01 - EP US); **B26D 1/5475** (2013.01 - EP US); **B26D 7/2614** (2013.01 - EP US); **D21G 9/0063** (2013.01 - EP US); **Y10T 83/2029** (2015.04 - EP US); **Y10T 83/2074** (2015.04 - EP US); **Y10T 83/2083** (2015.04 - EP US); **Y10T 83/4725** (2015.04 - EP US); **Y10T 83/9292** (2015.04 - EP US)

Citation (search report)

- [Y] EP 0554339 A1 19930811 - FIBRON MACHINE CORP [CA]
- [Y] EP 0141156 A1 19850515 - BELLMER GEB KG MASCHF [DE]

Cited by

DE102007053700A1; DE10045141A1; EP2058433A2

Designated contracting state (EPC)

DE FI SE

DOCDB simple family (publication)

DE 19537173 C1 19961219; CA 2187237 A1 19970407; CN 1152535 A 19970625; DE 59603214 D1 19991104; EP 0767272 A2 19970409; EP 0767272 A3 19970507; EP 0767272 B1 19990929; US 5799556 A 19980901

DOCDB simple family (application)

DE 19537173 A 19951006; CA 2187237 A 19961007; CN 96112646 A 19960923; DE 59603214 T 19960711; EP 96111142 A 19960711; US 70627196 A 19960904