

Title (en)

Device for changing printing-cylinder-sleeves of printing machines

Title (de)

Vorrichtung zum Wechseln von Druckzylinderhülsen in Druckmaschinen

Title (fr)

Dispositif de changement des manchons de cylindres d'imprimerie dans les machines à imprimer

Publication

**EP 0769373 B1 19990127 (DE)**

Application

**EP 95116394 A 19951018**

Priority

EP 95116394 A 19951018

Abstract (en)

[origin: EP0769373A1] The device has two bearing blocks (20) rotatably supporting the sleeve during operation of the printer. The sleeve has hollow bearing pins (16) rigidly fixed at both ends to fit in the blocks. A radial play is provided between the cylinder sleeve and shaft (12) running through them during operation of the machine. The sleeve mounted in the blocks freely rotates whilst the shaft is stationary. The shaft can be adjusted by an axial drive relative to the bearing blocks in the axial direction between the operating position and lift-out position.

IPC 1-7

**B41F 13/26**

IPC 8 full level

**B41F 13/24** (2006.01); **B41F 13/26** (2006.01); **B41F 13/34** (2006.01)

CPC (source: EP US)

**B41F 13/26** (2013.01 - EP US); **B41P 2217/15** (2013.01 - EP US)

Cited by

EP1025996A1; EP1000737A1; DE202016102779U1; CN110709248A; US6647880B2; US6523470B2; US6267056B1; US11001052B2; US11390067B2

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB IE IT LI LU NL SE

DOCDB simple family (publication)

**EP 0769373 A1 19970423**; **EP 0769373 B1 19990127**; AT E176194 T1 19990215; DE 59504993 D1 19990311; DK 0769373 T3 19990913; ES 2126830 T3 19990401; JP H09123396 A 19970513; US 5638754 A 19970617

DOCDB simple family (application)

**EP 95116394 A 19951018**; AT 95116394 T 19951018; DE 59504993 T 19951018; DK 95116394 T 19951018; ES 95116394 T 19951018; JP 23852296 A 19960821; US 68540796 A 19960724