

Title (en)  
Lock of the disengageable rotor type

Title (de)  
Schloss vom Typ eines entkuppelbaren Rotors

Title (fr)  
Verrou du type à rotor débrayable

Publication  
**EP 0769597 B1 20001206 (FR)**

Application  
**EP 96402198 A 19961015**

Priority  
FR 9512325 A 19951018

Abstract (en)  
[origin: EP0769597A1] The lock (10) has a main body (12) forming a fixed stator which is installed in a lock casing or vehicle door housing. It also has an intermediate stator (14), in which a rotor (16) rotates. An outlet part (18) is connected to a lock control mechanism. Locking parts (59), such as piston pairs, engage the rotor and the intermediate stator. This causes them to rotate together in the absence of a key and free the rotor from the stator after introduction of a key. The lock body consists of an external cylindrical annular skirt (20) closed at its axial front end by a bottom disc (24) with a central circular hole (26). The bottom has a notch (28) which emerges axially from the bottom side and opens radially towards the hole interior. The notch receives an indexing spherical ball (30) for indexing the intermediate stator relative to the body. The indexing ball immobilises rotation of the outlet part relative to the body when it is retracted.

IPC 1-7  
**E05B 17/04**

IPC 8 full level  
**E05B 17/04** (2006.01)

CPC (source: EP)  
**E05B 17/04** (2013.01)

Cited by  
DE102007023458A1; ES2178519A1; FR2882463A1; AU2006217995B2; US7987688B2; WO2006089844A1; WO2011057626A1; US9506273B2; US9745774B2; JP2008532217A

Designated contracting state (EPC)  
DE ES GB IT

DOCDB simple family (publication)  
**EP 0769597 A1 19970423; EP 0769597 B1 20001206**; DE 69611146 D1 20010111; DE 69611146 T2 20010621; ES 2153945 T3 20010316; FR 2740163 A1 19970425; FR 2740163 B1 19971121

DOCDB simple family (application)  
**EP 96402198 A 19961015**; DE 69611146 T 19961015; ES 96402198 T 19961015; FR 9512325 A 19951018