

Title (en)

Device for holding a wing ajar

Title (de)

Anlage um einen Flügel angelehnt zu halten

Title (fr)

Dispositif de maintien d'un ouvrant dans une position entrebâillée

Publication

**EP 0770751 B1 20000621 (FR)**

Application

**EP 96440080 A 19961009**

Priority

FR 9512903 A 19951027

Abstract (en)

[origin: EP0770751A1] The lock fitting for a door comprises a locking bolt consisting of an operating rod extending on a door rabbet. It is displaced by a drive mechanism activated by a control handle or key cylinder (12). The door is held ajar by a support (23), fixed on the door frame, on which is pivoted one (25) of the ends of a compass arm (26). The opposite end (27) of the compass arm has a guide pin (29) or a roller. This pin slides inside a strike plate (30) in a support (31) which is fixed to displace with the operating rod placed on the door. This limits the opening angle of the door relative to the door frame. The fastener disengages from the strike plate following displacement of the operating rod, acted on by the handle, consequent to it opening the door wider.

IPC 1-7

**E05C 17/24**

IPC 8 full level

**E05C 17/24** (2006.01)

CPC (source: EP)

**E05C 17/24** (2013.01)

Cited by

CN1298958C; US7278185B2; EP4174264A1; CN103161382A; EP2149661A1; CN101956361A; EP4174265A1; EP4006277A1; EP4174266A1; US11866966B2

Designated contracting state (EPC)

AT BE CH DE DK ES GB GR LI NL PT SE

DOCDB simple family (publication)

**EP 0770751 A1 19970502; EP 0770751 B1 20000621;** AT E194024 T1 20000715; DE 69608942 D1 20000727; DE 69608942 T2 20010201;  
ES 2149441 T3 20001101; FR 2740504 A1 19970430; FR 2740504 B1 19980227; GR 3034386 T3 20001229; PT 770751 E 20001130

DOCDB simple family (application)

**EP 96440080 A 19961009;** AT 96440080 T 19961009; DE 69608942 T 19961009; ES 96440080 T 19961009; FR 9512903 A 19951027;  
GR 20000402076 T 20000913; PT 96440080 T 19961009