

Title (en)

Silencer with variable damping characteristics

Title (de)

Schalldämpfer mit variabler Dämpfungscharakteristik

Title (fr)

Silencieux à caractéristiques d'amortissement variable

Publication

EP 0771939 B1 20000322 (DE)

Application

EP 96116731 A 19961018

Priority

DE 19540716 A 19951102

Abstract (en)

[origin: EP0771939A1] On the piston connecting rod (13) is a valve closure component. A pressure conduit (6.1) conducts the total gas pressure to the excess pressure side of the membrane (11.1). The operating box (10) has several chambers (14.1-4) separated by membranes (11.1-3). Each membrane is supported by a spring (12.1-3) and each chamber has a pressure connection (15.1-4). A further pressure conduit (6.2) conducts the static gas pressure to the low pressure side of the membrane. Both pressure conduits are integrated in the piston connecting rod and one of them issues in the head of the rod. The other pressure conduit issues at a distance from the head of the piston connecting rod and at a distance from the valve plate (5.1) laterally to the piston connecting rod.

IPC 1-7

F01N 1/16; F01N 1/08

IPC 8 full level

F01N 1/02 (2006.01); **F01N 1/08** (2006.01); **F01N 1/16** (2006.01)

CPC (source: EP US)

F01N 1/084 (2013.01 - EP US); **F01N 1/166** (2013.01 - EP US)

Cited by

US6564902B1; US6637545B1; WO0118365A1; WO9925962A1; WO0133049A1

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

DE 19540716 C1 19970417; DE 59604751 D1 20000427; EP 0771939 A1 19970507; EP 0771939 B1 20000322; JP H09166010 A 19970624;
US 5821474 A 19981013

DOCDB simple family (application)

DE 19540716 A 19951102; DE 59604751 T 19961018; EP 96116731 A 19961018; JP 28869596 A 19961030; US 73805996 A 19961025