

Title (en)

NOZZLE PLACEMENT IN MONOLITHIC DROP-ON-DEMAND PRINT HEADS

Title (de)

ANORDNUNG DER DÜSEN IN MONOLITHISCHEN AUF ABRUF ARBEITENDEN DRUCKKÖPFEN

Title (fr)

PLACEMENT DES BUSES DANS LES TETES MONOLITHIQUES D'IMPRESSION FONCTIONNANT EN GOUTTE-A-LA-DEMANDE

Publication

**EP 0772526 A2 19970514 (EN)**

Application

**EP 96911653 A 19960409**

Priority

- AU PN230795 A 19950412
- US 9604857 W 19960409

Abstract (en)

[origin: WO9632281A2] An improved print head construction for maintaining wafer strength along the line of nozzles at approximately 50 % of the normal wafer strength. This is achieved by dividing each row of nozzles into segments, and by displacing some of those segments (preferably every alternate segment) in the print direction. Displacement of the segment of nozzles is in the print direction so that the nozzles can still print the same pixels to the recording medium, simply by altering the time that the nozzles are provided with the particular information to be printed. The distance that the displaced segments are displaced is preferably slightly more than the width of the slot (or ink channel) in which the nozzles in the appropriate segment are formed.

IPC 1-7

**B41J 2/14; B41J 2/155**

IPC 8 full level

**B41J 2/175** (2006.01); **B41J 2/005** (2006.01); **B41J 2/14** (2006.01); **B41J 2/155** (2006.01); **B41J 2/16** (2006.01)

CPC (source: EP)

**B41J 2/005** (2013.01); **B41J 2/1433** (2013.01); **B41J 2/14451** (2013.01); **B41J 2/155** (2013.01); **B41J 2002/14475** (2013.01);  
**B41J 2202/11** (2013.01)

Citation (search report)

See references of WO 9632281A2

Designated contracting state (EPC)

DE GB

DOCDB simple family (publication)

**WO 9632281 A2 19961017; WO 9632281 A3 19961114**; AU PN230795 A0 19950504; EP 0772526 A2 19970514; JP H10501767 A 19980217

DOCDB simple family (application)

**US 9604857 W 19960409**; AU PN230795 A 19950412; EP 96911653 A 19960409; JP 53110696 A 19960409