

Title (en)

ENERGY TRANSFER SYSTEM BETWEEN A HOT SOURCE AND A COLD SOURCE

Title (de)

ENERGIEÜBERTRAGUNGSSYSTEM ZWISCHEN EINER WÄRMEQUELLE UND EINER KÄLTEQUELLE

Title (fr)

SYSTEME DE TRANSFERT D'ENERGIE ENTRE UNE SOURCE CHAUDE ET UNE SOURCE FROIDE

Publication

EP 0772757 B1 19980826 (FR)

Application

EP 95926430 A 19950726

Priority

- FR 9501004 W 19950726
- FR 9409459 A 19940729

Abstract (en)

[origin: WO9604517A1] A hot source (A) contains one assembly comprised of at least one capillary evaporator (1A) and at least one condenser (2B) having condensation surfaces with a large curvature radius, and a cold source (B) containing an assembly of the same nature (1B, 2B). The condensers are interconnected by means of a steam conduit (3) and the capillary evaporators are interconnected by means of a liquid conduit (4) so as to form a closed circuit wherein circulates a metered fluid amount so that the complete evaporation takes place in the "hot" evaporators and the complete condensation takes place in the "cold" condensers, the other elements being then inactive. The system is reversible and, consequently, interesting gains of weight and room can be achieved for a spatial utilisation.

IPC 1-7

F28D 15/02; **F28D 15/04**

IPC 8 full level

F28D 15/02 (2006.01); **F28D 15/04** (2006.01)

CPC (source: EP US)

F28D 15/043 (2013.01 - EP US)

Designated contracting state (EPC)

BE DE FR GB IT

DOCDB simple family (publication)

WO 9604517 A1 19960215; CA 2196045 A1 19960215; DE 69504357 D1 19981001; DE 69504357 T2 19990422; DE 772757 T1 19970925; EP 0772757 A1 19970514; EP 0772757 B1 19980826; FR 2723187 A1 19960202; FR 2723187 B1 19960927; JP H10503580 A 19980331; US 5842513 A 19981201

DOCDB simple family (application)

FR 9501004 W 19950726; CA 2196045 A 19950726; DE 69504357 T 19950726; DE 95926430 T 19950726; EP 95926430 A 19950726; FR 9409459 A 19940729; JP 50624196 A 19950726; US 79751097 A 19970129