

Title (en)

Method for controlling the breaking length in the transverse direction of a moving fibrous web

Title (de)

Verfahren zur Beeinflussung des Reisslängen-Querprofiles einer laufenden Faserstoffbahn

Title (fr)

Procédé pour régler la longueur de rupture dans le sens transversal d'une bande fibreuse en mouvement

Publication

**EP 0774540 A3 19980107 (DE)**

Application

**EP 96118249 A 19961114**

Priority

DE 19542873 A 19951117

Abstract (en)

[origin: EP0774540A2] In a process for making a web of paper with a substantially uniform cross-machine grammage profile and a substantially uniform cross-machine profile of another web characteristic, the latter profile is adjusted over the fibre area in such a way that the ratio of the breaking length in the direction of web travel to that in the cross-machine direction is substantially constant across the width of the web.

IPC 1-7

**D21F 9/00; D21F 1/02**

IPC 8 full level

**D21F 1/02** (2006.01); **D21F 9/00** (2006.01); **D21G 9/00** (2006.01)

CPC (source: EP US)

**D21F 1/02** (2013.01 - EP US); **D21G 9/0009** (2013.01 - EP US); **Y10S 162/11** (2013.01 - EP US)

Citation (search report)

- [A] EP 0475671 A2 19920318 - JAMES RIVER CORP [US]
- [X] EGELHOF D: "Der Einfluss des Stoffauflaufes auf Asymmetriefehler im Papier", DAS PAPIER, vol. 40, no. 7, July 1986 (1986-07-01), DARMSTADT, pages 313 - 318, XP002046187
- [A] DAHL H, HOLIK H, WEISSHUHN E.: "The influence of headbox flow conditions on paper properties and their constancy", TAPPI, vol. 71, no. 2, February 1988 (1988-02-01), NORCROSS (USA), pages 93 - 98, XP002046188

Cited by

DE10355687A1; DE10351295A1; DE29713272U1; DE19908973A1; EP1033437A3; US6179963B1; US6251225B1; US6536443B1

Designated contracting state (EPC)

DE FI SE

DOCDB simple family (publication)

**EP 0774540 A2 19970521; EP 0774540 A3 19980107; EP 0774540 B1 20020227**; DE 59608786 D1 20020404; US 6179963 B1 20010130

DOCDB simple family (application)

**EP 96118249 A 19961114**; DE 59608786 T 19961114; US 74691896 A 19961118