

Title (en)

APPARATUS AND METHODS FOR TWO-SIDED COATING OF ELONGATED STRIP ARTICLES

Title (de)

APPARAT UND VERFAHREN ZUR BEIDSEITIGEN BESCHICHTUNG VON BAHNNEN

Title (fr)

MACHINE A REVETIR LES DEUX FACES DE RUBANS ET PROCEDE ASSOCIE

Publication

EP 0775026 B1 19980826 (EN)

Application

EP 94916855 A 19940526

Priority

- CA 9400291 W 19940526
- US 6899093 A 19930527

Abstract (en)

[origin: WO9427739A1] Apparatus and procedure for coating both opposed major surfaces (19, 20) of an elongated strip article (10) with paint, lacquer, lubricant or the like, using two facing coating heads (30, 30') respectively having lands (32, 32'), between which the strip is advanced. Liquid coating material, delivered to the strip surfaces through elongated slits (36, 36') formed in the coating heads immediately upstream of the lands, is dragged out on the moving surfaces as layers metered between the lands and the strip. A load is continuously exerted (by devices such as air cylinders (64, 64')) on at least one of the lands during the coating operation for urging the lands against the applied coating layers.

IPC 1-7

B05C 5/02; B05C 9/04

IPC 8 full level

B05D 1/26 (2006.01); **B05C 5/02** (2006.01); **B05C 9/04** (2006.01)

CPC (source: EP US)

B05C 5/026 (2013.01 - EP US); **B05C 5/0295** (2013.01 - EP US); **B05C 9/04** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB IE IT LI LU NL SE

DOCDB simple family (publication)

WO 9427739 A1 19941208; AT E170108 T1 19980915; BR 9406660 A 19960130; CA 2162859 A1 19941208; CA 2162859 C 20000125; DE 69412865 D1 19981001; DE 69412865 T2 19990325; EP 0775026 A1 19970528; EP 0775026 B1 19980826; JP H09504730 A 19970513; US 5807434 A 19980915

DOCDB simple family (application)

CA 9400291 W 19940526; AT 94916855 T 19940526; BR 9406660 A 19940526; CA 2162859 A 19940526; DE 69412865 T 19940526; EP 94916855 A 19940526; JP 50005295 A 19940526; US 74790596 A 19961102