

Title (en)  
Device for aligning flat mail objects

Title (de)  
Vorrichtung zum Ausrichten von flachen Sendungen

Title (fr)  
Dispositif pour aligner des objets postaux plats

Publication  
**EP 0775657 A2 19970528 (DE)**

Application  
**EP 96112616 A 19960805**

Priority  
DE 19528829 A 19950805

Abstract (en)

The aligner comprises a base belt (1) and a cover belt (2). The letters (3) are moved standing on one edge. The cover belt in normal operation has a nominal speed of VN. There is a pair of rollers (5,6) with a common rotary axis (7) vertical to the belt's conveying direction. As the letter is covered only from behind by the cover belt, the rollers can locate on it in with a frictional engagement. As soon as a letter is secured by the rollers, a torque is exerted on it to alter its position in relation to the conveyor system. For this purpose, one of the rollers rotates with a nominal speed (VN), whilst the second roller has a different speed (V). The difference between the two speeds leads to the formation of a torque on the letter so that its position can be corrected where necessary.

Abstract (de)

Bei einer Vorrichtung zum Ausrichten von flachen Sendungen (3), die auf einer Kante stehend mittels eines Bändersystems gefördert werden, daß ein im wesentlichen horizontal angeordnetes Grundband (1) und ein aus Ober- und Unterband bestehendes Deckband (2) aufweist, zwischen denen die Sendungen (3) gefördert werden, ist vorgesehen, daß in einem vorgegebenen Abschnitt des Bändersystems ein angetriebenes Paar Rollen (5,6) vorgesehen ist, dessen gemeinsame Achse (7) im wesentlichen senkrecht zur Förderrichtung angeordnet ist, wobei die erste Rolle (5) oberhalb des Deckbandes (2) und die zweite Rolle (6) unterhalb des Deckbandes (2) derartig angeordnet ist, daß eine diesen Abschnitt passierende Sendung (3) reibschlüssig von den Rollen (5,6) gefaßt wird, und daß Drehgeschwindigkeit und/oder Orientierung der Rollen (5,6) derart veränderbar ist, daß ein die Lage der Sendung (3) relativ zum Bändersystem veränderndes Moment auf die Sendungen (3) ausübbbar ist, zur Korrektur der Sendungslage.  
<IMAGE>

IPC 1-7

**B65H 9/00**

IPC 8 full level

**B07C 1/06** (2006.01); **B65H 9/16** (2006.01)

CPC (source: EP)

**B07C 1/06** (2013.01)

Cited by

US7777148B2; US8020863B2; DE102012206784A1; WO2017000651A1

Designated contracting state (EPC)

DE FR GB IT NL

DOCDB simple family (publication)

**DE 19528829 A1 19970206**; **DE 19528829 C2 19980430**; DE 59606997 D1 20010705; EP 0775657 A2 19970528; EP 0775657 A3 19971105;  
EP 0775657 B1 20010530

DOCDB simple family (application)

**DE 19528829 A 19950805**; DE 59606997 T 19960805; EP 96112616 A 19960805