

Title (en)

High-strength austenitic heat-resisting steel having improved weldability

Title (de)

Hochfester wärmebeständiger austenitischer Stahl mit verbesserter Schweissbarkeit

Title (fr)

Acier thermorésistant austénitique à résistance élevée ayant une soudabilité améliorée

Publication

**EP 0780483 B1 20020417 (EN)**

Application

**EP 96120536 A 19961219**

Priority

- JP 33234195 A 19951220
- JP 13541296 A 19960529

Abstract (en)

[origin: EP0780483A1] A high-strength austenitic heat-resisting steel, having improved weldability, consisting of less than 0.05 wt% C, not more than 5 wt% Si, less than 2 wt% Mn, not more than 0.03 wt% P, not more than 0.005 wt% S, 15 to 20 wt% Cr, 6 to 15 wt% Ni, 1.5 to 10 wt% W, more than 0.1 up to 0.5 wt% Nb, 0.05 to 1.5 wt% V, more than 0.15 up to 0.4 wt% N, and the balance consisting of Fe and unavoidable impurities.

IPC 1-7

**C22C 38/44**; **C22C 38/46**; **C22C 38/48**

IPC 8 full level

**C22C 38/00** (2006.01); **C22C 38/18** (2006.01); **C22C 38/44** (2006.01); **C22C 38/46** (2006.01); **C22C 38/48** (2006.01)

CPC (source: EP)

**C22C 38/44** (2013.01); **C22C 38/46** (2013.01); **C22C 38/48** (2013.01)

Cited by

EP1215299A3; EP1471158A1; EP2832886A4; US9714459B2; US6918968B2

Designated contracting state (EPC)

DE ES FR SE

DOCDB simple family (publication)

**EP 0780483 A1 19970625**; **EP 0780483 B1 20020417**; DE 69620722 D1 20020523; DE 69620722 T2 20021205; JP 3388998 B2 20030324; JP H09228003 A 19970902

DOCDB simple family (application)

**EP 96120536 A 19961219**; DE 69620722 T 19961219; JP 13541296 A 19960529