

Title (en)

BRUSH SEAL WITH FOOL PROOFING AND ANTI-ROTATION TAB

Title (de)

BÜRSTENDICHTUNG MIT VERTRIEB- UND VERDREHSICHERUNGSNASE

Title (fr)

BALAI D'ETANCHEITE A PLAQUETTE PREVENANT LE DEREGLAGE ET INTERDISANT LA ROTATION

Publication

EP 0781385 A1 19970702 (EN)

Application

EP 95935073 A 19950922

Priority

- US 9512148 W 19950922
- US 31403494 A 19940928

Abstract (en)

[origin: WO9610143A1] A brush seal assembly (42) includes a tab (84) extending outward and engageable with a brush retainer (64). Various construction details are disclosed that provide a tab (84) that prevents rotation of the brush seal during use and also prevents reverse installation of the brush seal assembly (42). In a particular embodiment, a brush seal assembly (42) for installation within a carrier (58) includes a tab (84) that fits radially within a cut-out (92) in a retaining means (64). Engagement with the cut-out (92) prevents rotation. The tab (84) extends outward from the low pressured side of the brush seal assembly (42). If installed in a reverse orientation, the tab (84) engages the carrier (58) to block installation of the retaining means (64).

IPC 1-7

F16J 15/32; F01D 11/00

IPC 8 full level

F01D 5/08 (2006.01); **F01D 11/00** (2006.01); **F16J 15/16** (2006.01); **F16J 15/32** (2006.01)

CPC (source: EP US)

F01D 11/00 (2013.01 - EP US); **F16J 15/3288** (2013.01 - EP US)

Citation (search report)

See references of WO 9610143A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

WO 9610143 A1 19960404; DE 69506269 D1 19990107; DE 69506269 T2 19990415; EP 0781385 A1 19970702; EP 0781385 B1 19981125; JP 3721198 B2 20051130; JP H10506177 A 19980616; US 5597167 A 19970128

DOCDB simple family (application)

US 9512148 W 19950922; DE 69506269 T 19950922; EP 95935073 A 19950922; JP 51190696 A 19950922; US 31403494 A 19940928