

Title (en)

Thermally actuatable auxiliary electrical switch apparatus

Title (de)

Hitzeaktivierbare elektrische Hilfsschalter

Title (fr)

Interrupteur électrique auxiliaire activé par la chaleur

Publication

EP 0782163 A2 19970702 (EN)

Application

EP 96308920 A 19961209

Priority

US 886095 P 19951219

Abstract (en)

A thermally actuatable auxiliary switch (10, 10', 100) used with a refrigerator compressor system (60) has a generally U-shaped bimetallic element (12) mounted at one end on a base plate (16, 16', 102) and with a movable contact (28) mounted on the high expansion side (12a) of the bimetallic element in alignment with a stationary contact (32) mounted on a stationary contact support (18, 18', 116). A thermal generator (34) in the form of a PTC pill (36) wire-wound resistor (28), or other electrically energizable heater or in the form of a discharge tube (60e) of a compressor, provides heat to the bimetallic element (12) causing it to deflect after the solid state starter (50) has switched to its high resistance state to switch out the solid state starter while the compressor motor remains energized. <IMAGE>

IPC 1-7

H01H 61/00

IPC 8 full level

H01H 37/52 (2006.01); **H01H 61/00** (2006.01); **H02P 1/42** (2006.01); **F25B 31/02** (2006.01); **H01H 37/54** (2006.01); **H01H 61/02** (2006.01)

CPC (source: EP)

H01H 61/002 (2013.01); **F25B 31/02** (2013.01); **H01H 37/5427** (2013.01); **H01H 61/02** (2013.01); **H01H 2061/004** (2013.01)

Designated contracting state (EPC)

DE FR GB IT NL

DOCDB simple family (publication)

EP 0782163 A2 19970702; **EP 0782163 A3 19980729**; JP H09180610 A 19970711

DOCDB simple family (application)

EP 96308920 A 19961209; JP 33862496 A 19961218