

Publication

EP 0782930 A3 19970730

Application

EP 96890195 A 19961217

Priority

AT 496 U 19960104

Abstract (en)

[origin: EP0782930A2] The stamp (1) has pressure actuator (3) with arms (4) fitted to the side walls (5) of the housing (2). At least one securing component is horizontally displaceable in one of the arms. This component can engage at least one securing niche (8) in the adjacent side wall of the housing. The securing component fixes the actuator in predetermined positions along its movement path on the housing. The niche on its upper edge has a back cut, and the securing component is formed by a sprung tongue (7), the free end of which can be pressed into the niche and hooked behind the back cut.

IPC 1-7

B41K 1/40

IPC 8 full level

B41K 1/36 (2006.01); **B41K 1/40** (2006.01); **B41K 1/00** (2006.01)

CPC (source: EP US)

B41K 1/40 (2013.01 - EP US)

Citation (search report)

- [A] DE 1113221 B 19610831 - FRITZ SCHOETTGEN
- [DA] AT 390230 B 19900410 - SKOPEK KARL [AT]

Designated contracting state (EPC)

AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0782930 A2 19970709; EP 0782930 A3 19970730; EP 0782930 B1 19990331; AT 1241 U1 19970127; AT E178275 T1 19990415; DE 59601553 D1 19990506; HU 216862 B 19990928; HU 9700011 D0 19970228; HU P9700011 A1 19970929; PL 182590 B1 20020131; PL 317809 A1 19970707; RU 2164208 C2 20010320; US 5727467 A 19980317

DOCDB simple family (application)

EP 96890195 A 19961217; AT 496 U 19960104; AT 96890195 T 19961217; DE 59601553 T 19961217; HU P9700011 A 19970103; PL 31780997 A 19970102; RU 96124761 A 19961230; US 76319196 A 19961210