

Title (en)

Process for the dewatering, deacidification and degasolination of natural gas, using a mixture of solvents

Title (de)

Verfahren zur Entfernung von Wasser, Säuren und Benzin aus Erdgas, unter Verwendung eines Lösungsmittelgemisches

Title (fr)

Procédé de déshydratation, de désacidification et de dégazolinage d'un gaz naturel, utilisant un mélange de solvants

Publication

EP 0783031 A1 19970709 (FR)

Application

EP 96402909 A 19961227

Priority

FR 9515626 A 19951228

Abstract (en)

A process for the natural gas dehydration and/or de-acidification and/or gasoline removal involves: (a) contacting a fraction of the gas with an aqueous phase containing MeOH, to produce a gaseous effluent charged with MeOH; (b) contacting the gas with a solvent mixture comprising MeOH, water and a solvent heavier than MeOH, the effluent being partially free from acid gases; (c) regenerating the mixture of solvents from (b) by pressure reduction and/or heating, liberating the acid gases, the re-generated solvent mixture being re-cycled to step (b); and (d) cooling the gas from step (b) to produce an aqueous phase containing MeOH which is re-cycled to (a). In an example, the composition of the natural gas was (in kg/h): water 60.55; N₂ 782.37; CO₂ 8770.15; CH₄ 31699.87; C₂H₆ 5210.67; C₃H₈ 3088.88; i-C₄H₁₀ 625.43; n-C₄H₁₀ 1024.58; iso-C₅H₁₂ 330.39; n-C₅H₁₂ 297.37; n-C₆H₁₄ 118.29; n-C₇H₁₆ 343.99. Total = 52352.54 The gas to be treated is admitted at (1), at 30 degrees C. and 70 bars and flow rate 52352 kg/h. 50% of the gas was injected into the contact column (C1) via (2), and a solution containing 65% wt. of MeOH in water, at 159 kg/h and 30 degrees C., was injected counter-currently via (3). From the base of C1 an aqueous phase was eliminated (40) containing 12 ppm of MeOH at 60 kg/h. From the head of (C1), the gas charged with MeOH was evacuated via (4) and mixed with gas which had not been passed through (C1). The gas obtained was sent via (6) to column (C2). A solution containing 20% wt. of MeOH and 20% wt. of diethanolamine in water was injected counter-currently via (7) at 40 degrees C. with a flow rate of 117409 kg/h. From the base of (C2) the solvent mixture charged with CO₂ was recovered by 8 at 46 degrees C. The gas evacuated from the head of (C2) by (9) contained only 1.8% wt. of CO₂. The gas was cooled by (E3) and (E4) at -26 degrees C. The triphase mixture obtained was separated in the chamber (B2), and the treated gas evacuated via (14) at 44889 kg/h. The liquid hydrocarbon phase obtained was evacuated at (15) and the aqueous phase containing MeOH was partially re-cycled to (C1) via (41) the other part (75%) being sent to the chamber (B20). The solvent mixture charged with CO₂ was expanded to 10 bars by the valve (V1), then sent to (B1). The liquid phase from (B1) was sent via (10) to exchanger (E1), where it was re-heated to 60 degrees C. It was then expanded to 1.5 bar and injected into the distillation column (D1). This was cooled at the head to 40 degrees C and heated at the base. The solvent mixture recovered via (12) at 80 degrees C. was pumped (P1) then cooled in (E1) and (E2) before being re-cycled to (C2). The gas from the head of (D1), via (11), was cooled to -26 degrees C after passing through (E5). The chamber (B20) allowed separation of a liquid phase containing MeOH and water, and a gaseous phase comprising CO₂. The aqueous phase was re-cycled to (C2) via (43). The gaseous phase was evacuated via (23).

Abstract (fr)

On décrit un procédé de déshydratation, de désacidification et de dégazolinage d'une gaz caractérisé en ce que : (a) au moins une fraction du gaz est mise en contact avec une phase aqueuse contenant du méthanol, le gaz étant ainsi chargé en méthanol à la sortie de l'étape (a) ; (b) le gaz sortant de l'étape (a) est mis en contact avec un mélange de solvants comprenant du méthanol, de l'eau et un solvant plus lourd que le méthanol, le gaz sortant de l'étape (b) étant ainsi au moins en partie débarrassé des gaz acides qu'il contient à l'entrée dans le procédé ; (c) le mélange de solvants provenant de l'étape (b) chargé en gaz acides est au moins en partie régénéré par réduction de la pression et/ou chauffage en libérant au moins en partie les gaz acides, le mélange de solvants au moins partiellement régénéré, étant à l'issue de l'étape (c), recyclé à l'étape (b) ; et (d) le gaz provenant de l'étape (b) est réfrigéré en produisant au moins une phase aqueuse contenant du méthanol, qui est au moins en partie recyclée à l'étape (a). <IMAGE>

IPC 1-7

C10L 3/10

IPC 8 full level

C10G 5/04 (2006.01); **C10G 5/06** (2006.01); **C10L 3/10** (2006.01)

CPC (source: EP US)

C10L 3/10 (2013.01 - EP US); **C10L 3/102** (2013.01 - EP US)

Citation (search report)

- [A] FR 2550956 A1 19850301 - PETROLES CIE FRANCAISE [FR]
- [A] DE 1794353 A1 19730215 - KNAPP HELMUT PROF DR PHYS
- [A] FR 2600554 A1 19871231 - ELF AQUITAINE [FR]

Cited by

FR2820430A1; CN104812876A; US6666908B2

Designated contracting state (EPC)

DE DK GB IT

DOCDB simple family (publication)

EP 0783031 A1 19970709; **EP 0783031 B1 20010926**; CA 2194083 A1 19970629; CA 2194083 C 20060606; DE 69615522 D1 20011031; DE 69615522 T2 20020425; DK 0783031 T3 20011126; FR 2743083 A1 19970704; FR 2743083 B1 19980130; JP 4264594 B2 20090520; JP H09194851 A 19970729; NO 314901 B1 20030610; NO 965609 D0 19961227; NO 965609 L 19970630; US 5782958 A 19980721

DOCDB simple family (application)

EP 96402909 A 19961227; CA 2194083 A 19961227; DE 69615522 T 19961227; DK 96402909 T 19961227; FR 9515626 A 19951228; JP 34925596 A 19961227; NO 965609 A 19961227; US 77744296 A 19961230