

Title (en)

IMPROVED BORESIGHT WITH SINGLE-BEAM TRIAXIAL MEASUREMENT

Title (de)

VERBESSERTE VISIEREINRICHTUNG MIT EINSTRAHLIG-DREIACHSIGER MESSUNG

Title (fr)

SYSTEME AMELIORE DE LIGNE DE VISEE A MESURE TRIAXIALE UTILISANT UN SEUL FAISCEAU

Publication

EP 0783663 A1 19970716 (EN)

Application

EP 95938138 A 19950929

Priority

- US 9512668 W 19950929
- US 31543894 A 19940930

Abstract (en)

[origin: WO9610729A1] Optical transceiver apparatus for measuring angular misalignment between two bodies in elevation, azimuth and roll utilizes a light transmitter (40) coupled to a first body such as an aircraft fuselage reference and a light receiver (12) coupled to a second body such as an aircraft wing or pylon. The receiver has an elevation/azimuth (EL/AZ) channel and a roll channel sharing a common objective lens, wherein a beam splitter (45) splits the beam generated by the laser diode (10) between the two channels. In the EL/AZ channel lenses are used to focus light onto a position sensitive detector (PSD) (46), while in the roll channel, a Thompson beam-splitting prism (13') or other suitable optimal element divides the two planes of polarization which are then focused on light detectors (16).

IPC 1-7

G01B 11/26; **G01C 1/00**

IPC 8 full level

G01B 11/26 (2006.01); **G01C 1/00** (2006.01); **H01L 31/16** (2006.01)

CPC (source: EP)

G01B 11/26 (2013.01); **G01C 1/00** (2013.01)

Cited by

CN110749287A

Designated contracting state (EPC)

BE DE DK ES FR GB GR NL SE

DOCDB simple family (publication)

WO 9610729 A1 19960411; AU 3888195 A 19960426; EP 0783663 A1 19970716; EP 0783663 A4 19990414; JP H10506992 A 19980707

DOCDB simple family (application)

US 9512668 W 19950929; AU 3888195 A 19950929; EP 95938138 A 19950929; JP 51211295 A 19950929