

Title (en)
Thermal transfer ribbon

Title (de)
Thermotransferband

Title (fr)
Ruban pour le transfert thermique

Publication
EP 0785086 B1 19990414 (DE)

Application
EP 96116958 A 19961022

Priority
DE 19548033 A 19951221

Abstract (en)
[origin: CA2193023A1] The invention relates to a thermo-transfer ribbon with a customary carrier, with a wax-based layer of a thermo-transfer color formed on one side of the carrier and an additional layer located between the carrier and the wax-based layer. This thermo-transfer ribbon distinguishes itself in that the additional layer is a wax-based separation layer A) for the wax-based layer B) of the thermotransfer color wherein the waxes of the wax-based layer have a melting point of approximately 70.degree. C to 110.degree. C, and wherein in both layers A) and B) a waxesoluble polymer is finely dispersed. The advantages of this thermo-transfer ribbon include the fact that there is no need for development of a topcoat of a dual-layer thermo-transfer color, and that satisfactory prints are obtained with the thermo-printing process.

IPC 1-7
B41M 5/38; B41J 31/00

IPC 8 full level
B41J 31/00 (2006.01); **B41J 31/06** (2006.01); **B41M 5/395** (2006.01); **B41M 5/40** (2006.01); **B41M 5/44** (2006.01)

CPC (source: EP US)
B41J 31/06 (2013.01 - EP US); **B41M 5/395** (2013.01 - EP US); **B41M 5/44** (2013.01 - EP US); **Y10S 428/913** (2013.01 - EP US); **Y10S 428/914** (2013.01 - EP US); **Y10T 428/31511** (2015.04 - EP US); **Y10T 428/31551** (2015.04 - EP US); **Y10T 428/31786** (2015.04 - EP US); **Y10T 428/31935** (2015.04 - EP US)

Cited by
EP0885749A3

Designated contracting state (EPC)
CH DE FR GB IT LI

DOCDB simple family (publication)
DE 19548033 A1 19970703; CA 2193023 A1 19970622; DE 59601658 D1 19990520; EP 0785086 A1 19970723; EP 0785086 B1 19990414; US 5827617 A 19981027

DOCDB simple family (application)
DE 19548033 A 19951221; CA 2193023 A 19961216; DE 59601658 T 19961022; EP 96116958 A 19961022; US 76382996 A 19961211